



## Config. Code

0181 - H - A B C 0- D - E

The characters are placeholders for the correspondingly keys of selections from the key tables.

0181 - H - A B C 0- D - E = Type

Type	Configuration key
protection class 1	X

0181 - H - A B C 0- D - E = Terminals

Terminal L	Configuration key
Blade terminal (4.8 x 0.8 mm)	8
Blade terminal (6.3 x 0.8 mm)	9
screw terminal	A

0181 - H - A B C 0- D - E = Terminals

Terminal N	Configuration key
Blade terminal (4.8 x 0.8 mm)	8
Blade terminal (6.3 x 0.8 mm)	9
screw terminal	A

Symbols similar as in table A

0181 - H - A B C 0- D - E = Terminals

Terminal Ground	Configuration key
Blade terminal (4.8 x 0.8 mm)	8
Blade terminal (6.3 x 0.8 mm)	9
screw terminal	A

Symbols similar as in table A

0181 - H - A B C 0- D - E = Color

Color	Configuration key
jet black; RAL9005	A
light grey; RAL7035	C

0181 - H - A B C 0- D - E = Style

Style	Configuration key
flange with countersunk holes	1
flange with through holes	2

## Variants

Config. Code	Description	Order Number
0181-X-8880-A-1	0181, IEC Appliance Inlet C16A, 155°C, version: 1, L: Blade terminal (4.8 x 0.8 mm), N: Blade terminal (4.8 x 0.8 mm), ground: Blade terminal (4.8 x 0.8 mm), color: jet black; RAL9005, design: flange with countersunk holes, dimension X: , features:	6172.0002
0181-X-8880-C-1	0181, IEC Appliance Inlet C16A, 155°C, version: 1, L: Blade terminal (4.8 x 0.8 mm), N: Blade terminal (4.8 x 0.8 mm), ground: Blade terminal (4.8 x 0.8 mm), color: light grey; RAL7035, design: flange with countersunk holes, dimension X: , features:	6172.0003
0181-X-9990-A-1	0181, IEC Appliance Inlet C16A, 155°C, version: 1, L: Blade terminal (6.3 x 0.8 mm), N: Blade terminal (6.3 x 0.8 mm), ground: Blade terminal (6.3 x 0.8 mm), color: jet black; RAL9005, design: flange with countersunk holes, dimension X: , features:	6172.0004
0181-X-9990-C-1	0181, IEC Appliance Inlet C16A, 155°C, version: 1, L: Blade terminal (6.3 x 0.8 mm), N: Blade terminal (6.3 x 0.8 mm), ground: Blade terminal (6.3 x 0.8 mm), color: light grey; RAL7035, design: flange with countersunk holes, dimension X: , features:	6172.0005
0181-X-AAA0-A-1	0181, IEC Appliance Inlet C16A, 155°C, version: 1, L: screw terminal, N: screw terminal, ground: screw terminal, color: jet black; RAL9005, design: flange with countersunk holes, dimension X: , features:	6172.0006
0181-X-AAA0-C-1	0181, IEC Appliance Inlet C16A, 155°C, version: 1, L: screw terminal, N: screw terminal, ground: screw terminal, color: light grey; RAL7035, design: flange with countersunk holes, dimension X: , features:	6172.0007

The listed variants should be available from stock. Other versions on request [www.schurter.com/contact](http://www.schurter.com/contact)

Packaging unit 50 Pcs

## Mating Outlets/Connectors

Category / Description

[ConnectorOverview complete](#)

IEC Connector C15A, Rewireable, Straight	0102
IEC Connector C15A, Rewireable, Straight	0102-G
IEC Connector C15A, Rewireable, Angled	0112

[Connectorfurther types to0181](#)