

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [75556-1501](#)  
**Status:** **Active**  
**Overview:** EXTreme PowerMass™  
**Description:** EXTreme PowerMass™ 0.13mm Pitch, 150A Module, 1 Circuit, Right Angle Plug, Long Blade Type, Tail Length 3.81mm, Lead-Free, No Pegs

**Documents:**

[3D Model](#) [Application Specification AS-75541-100 \(PDF\)](#)  
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

**Agency Certification**


CSA LR19980  
 UL E29179

**General**

Product Family PCB Headers  
 Series [75556](#)  
 Application Board-to-Board, Power  
 Comments 150A Module Tin Tails  
 Overview [EXTreme PowerMass™](#)  
 Product Name EXTreme PowerMass™  
 UPC 800756930794

**Physical**

(p)ower-(s)ignal Configuration 1p - 0s  
 Breakaway No  
 Circuits (Loaded) 4  
 Circuits (maximum) 4  
 Durability (mating cycles max) 50  
 First Mate / Last Break No  
 Flammability 94V-0  
 Glow-Wire Compliant No  
 Guide to Mating Part No  
 Keying to Mating Part None  
 Lock to Mating Part No  
 Material - Metal Copper-Nickel-Silicon  
 Material - Plating Mating Gold  
 Material - Plating Termination Tin  
 Number of Rows 1  
 Orientation Right Angle  
 PC Tail Length 3.81mm  
 PCB Locator Yes  
 PCB Retention None  
 PCB Thickness - Recommended 2.40mm  
 Packaging Type Tray  
 Pitch - Mating Interface N/A  
 Pitch - Termination Interface 1.60mm  
 Plating min - Mating 0.762µm  
 Plating min - Termination 2.540µm  
 Polarized to Mating Part No  
 Polarized to PCB Yes  
 Shrouded Closed Ends  
 Stackable No  
 Surface Mount Compatible (SMC) Yes  
 Temperature Range - Operating -40°C to +105°C  
 Termination Interface: Style Through Hole



**EU RoHS**

**ELV and RoHS  
 Compliant**  
**REACH SVHC  
 Not Reviewed**  
**Low-Halogen Status  
 Not Reviewed**

**China RoHS**



**Need more information on product  
 environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
 For a multiple part number RoHS Certificate of  
 Compliance, [click here](#)

Please visit the [Contact Us](#) section for any  
 non-product compliance questions.

**Search Parts in this Series**

[75556Series](#)

**Mates With**

[755455000](#) EXTreme PowerMass™  
 Receptacle, [755455001](#) EXTreme  
 PowerMass™ Receptacle

**Electrical**

Current - Maximum per Contact	150A
Voltage - Maximum	600V

**Material Info****Reference - Drawing Numbers**

Application Specification	AS-75541-100
Sales Drawing	SD-75556-100

This document was generated on 10/19/2012

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**