

# P.C. JACKS-CLOSED ENTRY-PRESS MOUNT

**09-9100-1-XX**      **P.C. JACK FOR .060 PIN**

BASIC PART NO.      FINISH

.304 MIN. HOLE DEPTH FOR .060 PIN ±.001

.100 ±.010      .250      .047      .070      .119

.132 ±.002 DIA. KNURL      BERYLLIUM COPPER SPRING INSERT CAPTIVATED

ACCEPTS .060, .061, AND .062 PINS\*      BOARD THICKNESS .031 TO .156

RECOMMENDED MOUNTING HOLE .128+.001/-.002(#30 DRILL)

\*USE ONE SIZE PIN ONLY-NOT RECOMMENDED FOR SMALLER PIN  
USE AFTER LARGER PIN HAS BEEN USED

**09-9101-1-XX**      **P.C. JACK FOR .080 PIN**

BASIC PART NO.      FINISH

0.312      0.100 ± 0.010      0.333 MIN. HOLE DEPTH FOR 0.080 PIN ±0.001

0.047      0.070      0.143

0.139      BERYLLIUM COPPER SPRING INSERT CAPTIVATED

0.155 ±0.002

ACCEPTS .080 PIN      BOARD THICKNESS .031 TO .250

RECOMMENDED MOUNTING HOLE .151+.001/-.002 DIA.

CALL  
**CONCORD**<sup>®</sup>  
 FOR  
 UNSURPASSED  
 QUALITY

**MATERIAL**      Body: Brass per ASTM B16      Spring Contact: Beryllium Copper per ASTM B194

FINISH	Part Number/Finish Code	Body Finish	Spring Contact Finish
	09-9XXX-X-03	Gold per ASTM B488	Gold per ASTM B488
	04	Electro-Tin per ASTM B545	Electro-Tin per ASTM B545
	06	Electro-Tin per ASTM B545	Gold per ASTM B488
	063	Bright Tin-Lead per ASTM B545	Gold per ASTM B488
	088	Bright Tin-Lead per ASTM B545	Bright Tin-Lead per ASTM B545



FOR ADDITIONAL SIZES AND MATERIALS, CONTACT FACTORY

800-847-4162 (Outside N.Y.S.)  
 Ph: 212-777-6571 Fax: 212-991-0161  
 sales@concord-electronics.com  
 engineering@concord-electronics.com