



Pushing Performance

## Han 24B-AK with stainless-steel cord



|                    |   |
|--------------------|---|
| Part number        | 09 30 024 5417  |
| Specification      | Han 24B-AK with stainless-steel cord  |
| HARTING eCatalogue | <a href="https://b2b.harting.com/09300245417">https://b2b.harting.com/09300245417</a> |

### Identification

|                                 |                               |
|---------------------------------|-------------------------------|
| Category                        | Hoods/Housings                |
| Series of hoods/housings        | Han <sup>®</sup> B            |
| Type of hood/housing            | Protection cover              |
| Description of hood/<br>housing | for bulkhead mounted housings |
|                                 | for surface mounted housings  |
|                                 | Metal                         |
|                                 | With fixing cord              |
| Type                            | Low construction              |
|                                 | High construction             |

### Version

|                      |   |
|----------------------|---|
| Locking type         | Double locking lever                              |
| Size                 | 24 B  |
| Field of application | Standard hoods/housings for industrial connectors |

### Technical characteristics

|  |                 |
|--|-----------------|
| Limiting temperature                   | -40 ... +125 °C |
| Degree of protection acc. to IEC 60529 | IP65            |
| Type rating acc. to UL 50 / UL 50E     | 4               |
|  | 4X              |
|  | 12              |

### Material properties

|                             |           |
|-----------------------------|-----------|
| RoHS                        | compliant |
| ELV status                  | compliant |
| China RoHS                  | e         |
| REACH Annex XVII substances | No        |
| REACH ANNEX XIV substances  | No        |
| REACH SVHC substances       | No        |



Pushing Performance

## Specifications and approvals

|           |        |
|-----------|--------|
| Approvals | DNV GL |
|-----------|--------|

## Commercial data

|                                |          |
|--------------------------------|----------|
| Packaging size                 | 1        |
| Net weight                     | 31.6 g   |
| Country of origin              | Germany  |
| European customs tariff number | 85389099 |