

## USBC 3.2Type G.2x2 C-cable,2xIP20,0,5m



Image is for illustration purposes only. Please refer to product description.

Part number	09 45 145 5900
Specification	USBC 3.2Type G.2x2 C-cable,2xIP20,0,5m
HARTING eCatalogue	<a href="https://b2b.harting.com/09451455900">https://b2b.harting.com/09451455900</a>

### Identification

Category	System cabling
Series	USB
Element	Cable assemblies
Specification	Pre-assembled on both sides
Connector 1	USBC 3.2 Gen. 2x2
	Type C
	Male IP20
Connector 2	USBC 3.2 Gen. 2x2
	Type C
	Male IP20
Type of cable	Copper cable (round)
Features	supports USB Power Delivery (USB-PD)

### Version

Cable length	0.5 m
Number of cores	24
Shielding	Shielded

### Technical characteristics

Rated current	5 A
Rated voltage	20 V
Data rate	≤20 Gbit/s
Mating cycles	≥10,000



Pushing Performance  
Since 1945

## Technical characteristics

Cable diameter	4.5 mm ± 0.2 mm
Vibration resistance	Category 1B acc. to IEC 61373
Shock resistance	Category 1B acc. to IEC 61373

## Material properties

Material (cable)	PVC
Colour (cable)	Black
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Nickel

## Commercial data

Packaging size	1
Net weight	25 g
Country of origin	China
European customs tariff number	85444290
eCl@ss	27060390 Ready-made data cable (unspecified)