

## Han3A RJ45 10G Cat6 PFT insert 8p



Image is for illustration purposes only. Please refer to product description.

Part number	09 45 200 1560
Specification	Han3A RJ45 10G Cat6 PFT insert 8p
HARTING eCatalogue	<a href="https://b2b.harting.com/09452001560">https://b2b.harting.com/09452001560</a>

### Identification

Category	Connectors
Series	RJ45
Element	Inserts

### Version

Size	Han <sup>®</sup> 3 A
Shielding	Fully shielded, 360° shielding contact

### Technical characteristics

Transmission characteristics	Cat. 6 Class E up to 250 MHz
Data rate	10 Mbit/s
	100 Mbit/s
	1 Gbit/s
	10 Gbit/s
Limiting temperature	-40 ... +70 °C
Mating cycles	≥500

### Material properties

RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained



Pushing Performance  
Since 1945

## Material properties

California Proposition 65 substances	Yes
California Proposition 65 substances	Antimony trioxide
California Proposition 65 substances	Lead
California Proposition 65 substances	Nickel

## Specifications and approvals

Approvals	DNV GL
UL / CSA	UL 1977 ECBT2.E102079 CSA-C22.2 No. 182.3 ECBT8.E102079
PROFINET	Yes

## Commercial data

Packaging size	1
Net weight	25.27 g
Country of origin	Romania
European customs tariff number	85366990
GTIN	5713140059511
eCl@ss	27440205 Contact insert for industrial connectors