

2.5 SIGNAL MATE CONN PLUG HSG

1. PURPOSE 目的

Define the packaging specification and packaging method of 2.5 SIGNAL MATE CONN PLUG HSG.

订定 2.5 SIGNAL MATE CONN PLUG HSG 产品之包装规格及包装方式。

2. APPLICABLE PRODUCT 适用范围

Product Part Number	Description
X-1376477-X	2.5 SIGNAL MATE CONN PLUG HSG

3. PACKAGING MATERIAL 包装材料

Package	Part No.	Description	Usage		
			X-1376477-5/6/7	X-1376477-3/4	X-1376477-2
INNER	9-720996-2	POLY BAG	1/300	1/400	1/600
	623865-4	BAG LABEL	1/300	1/400	1/600
MIDDLE	720992-1	URETHANE	5/1200	5/1600	5/2400
	912013-2	INNER BOX	1/1200	1/1600	1/2400
	623865-4	MIDDLE LABEL	1/1200	1/1600	1/2400
OUTER	1-912011-5	SHIPPING BOX	1/2400	1/3200	1/4800
	623865-5	OUTER LABEL	1/2400	1/3200	1/4800

	Inner	Middle	Outer
LABEL	623865-4	623865-4	623865-5
SEALING	Wire tie	Tape	Tape

4. PACKAGING QUANTITY 包装数量

	Inner	Middle	Outer
X-1376477-5/6/7	300 pcs/bag	1200 pcs/inner box	2400 pcs/shipping box
X-1376477-3/4	400 pcs/bag	1600 pcs/inner box	3200 pcs/shipping box
X-1376477-2	600 pcs/bag	2400 pcs/inner box	4800 pcs/shipping box

DR	CHK	APVD
Sam Wu	Jason Gong	Ansin Yang

5. PACKAGING METHOD 包装方法

5.1. Place an inner label to the middle of a polybag.

在一个塑料袋的中间贴上内标签。

5.2. Count products qty as 4 , put into a bag.

按4中规定数量称重或数数后装入一塑料袋中。

5.3. Tie the bag with a piece of plastic wire.

用一根塑胶带扎好袋口。

5.4. Set up an inner box.

折叠好一个内盒。

5.5. Place three pieces of foam into inner box of bottom.

在内盒的底部放入三块海绵。

5.6. Place 4 loaded bags into inner box.

将4袋装有产品的塑料袋竖放入内盒中。

5.7. Place two pieces of foam on top of product.

接着在产品的上面放入二块海绵。

5.8. Tuck closed top flap of inner box.

盒上盒盖。

5.9. Place a middle label to the top right corner.

在内盒的右上角贴上中标签。

5.10. Set up a box & secure bottom flaps with tape.

折叠好一个包装箱，并用胶带封好箱底。

5.11. Place 2 inner boxes full of products into the shipping box.

将两个包装好产品的内盒按是一方向放入外箱中。

5.12 Seal the box with tape. And place product identification label in "product id" marked on box.

用胶带封箱，在箱中印有“PRODUCT ID”标识处贴上外标签。