




[Home](#) > [Products](#) > [Modular Jacks & Plugs](#) > [Product Feature Selector](#) > Product Details

# 1-1734509-4 Product Details

[Share](#) [Print](#) [Email](#)


## PCB Mounted Jacks - Single Port, Multi-port and Stacked

RJ45,8P8C,Reverse,T&R,50u"

**1-1734509-4**

TE Internal Number: 1-1734509-4

[Pricing & Availability](#)
[Request Sample](#)
[Add to My Part List](#)
[Buy Product through Distributor](#)
[Feedback](#)

Active

[View 3D PDF](#)

### Product Highlights [View All](#)

- Connector
- Preloaded
- Single Port Configuration
- 1 x 1 Jack Configuration
- Jack Type = RJ45

[Documents](#) | [Features](#) | [Compliance](#)

**Please Note:**  
Use the Product Drawing for all design activity

Product Type Features	
Product Type	Connector
Jack Type <sup>?</sup>	RJ45
PCB Mounting Orientation <sup>?</sup>	Side Entry (Right Angle)
PCB Mount Style <sup>?</sup>	Through Hole
Performance Category <sup>?</sup>	Cat 3
LED <sup>?</sup>	Without
Grounding Options <sup>?</sup>	PCB Ground
Panel Stops <sup>?</sup>	Without
Keyed <sup>?</sup>	No
Profile <sup>?</sup>	Low
Color <sup>?</sup>	Black
Latch Style	Standard

Mechanical Attachment	
Panel Mount Retention <sup>?</sup>	With
Flanged	No

Termination Features	
Termination Method to PC Board <sup>?</sup>	Solder

Dimensions	
Height (mm [in]) <sup>?</sup>	11.30 [0.445]
PCB Tail Length (mm [in]) <sup>?</sup>	2.20 [0.087]
PCB Thickness, Recommended (mm [in])	1.57 [0.062]

Body Features	
Inverted Jack Face <sup>?</sup>	No
Shield Plating	Tin
LED Lightpipe Material	Copper Alloy
PCB Ground Tab Location (mm [in])	4.35 [0.171]

Contact Features	
Solder Tail Contact Plating <sup>?</sup>	Tin over Nickel
Contact Plating, Mating Area, Material <sup>?</sup>	Gold (50)
Contact Base Material	Phosphor Bronze

Housing Features	
Housing Material	High Temperature Thermoplastic

Configuration Features	
Preloaded	Yes
Port Configuration	Single
Jack Configuration <sup>?</sup>	1 x 1
Number of Positions <sup>?</sup>	8
Shielded <sup>?</sup>	Yes
Number of Contacts Loaded	8
Number of PCB Ground Tabs	2

Industry Standards	
RoHS/ELV Compliance <sup>?</sup>	RoHS compliant, ELV compliant
Lead Free Solder Processes <sup>?</sup>	Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
RoHS/ELV Compliance History	Always was RoHS compliant
UL Flammability Rating	UL 94V-0

Identification Marking	
LED Position 3 Color <sup>?</sup>	None

Packaging Features	
Packaging Method	Tape & Reel

Product Availability	
Region	Asia, North America

Other	
Brand	AMP

### Related Products

Not quite the product you're looking for?  
[Find Similar Products](#)

[View Part in Product Feature Selector](#)

[Check for Tooling](#)

### Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)
- [Global Accessibility Statement](#)

### Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

### Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

### Keep Me Informed

