

**LUMOTAST 75 IP40 - Illuminated pushbutton, flush lens, rectangular collar, latching, housing****1.15.108.152/0000****General information**

|                 |             |
|-----------------|-------------|
| Form of lens    | flat lens   |
| Form of collar  | rectangular |
| Color of collar | black       |

**Dimensions**

|                  |                   |
|------------------|-------------------|
| Length of collar | 24 mm             |
| Width of collar  | 18 mm             |
| Overall height   | 7.5 mm            |
| Mounting depth   | 41.5/49.5/57.5 mm |
| Mounting hole    | 16.2 mm           |

**Mechanical design**

|                     |                            |
|---------------------|----------------------------|
| Mounting            | ring nut                   |
| Terminals           | solder terminals           |
| Contact system      | snap-action bridge contact |
| Contact function    | latching                   |
| Contact arrangement | 2 NC + 2 NO                |
| Contact materials   | Ag                         |
| Illumination        | LED                        |
| Lamp socket         | T 4.5                      |

**Mechanical characteristics**

|                      |             |
|----------------------|-------------|
| Operating force max. | 3 ... 6.5 N |
| Operating travel     | 2.7 mm      |
| Switching travel NC  | 1.6 mm      |
| Switching travel NO  | 0.9 mm      |
| Robustness max.      | 100 N       |

**Electrical characteristics**

|                                      |        |
|--------------------------------------|--------|
| Rated voltage AC max.                | 250 V  |
| Rated voltage DC max.                | 230 V  |
| Rated voltage AC/DC min.             | 12 V   |
| Rated current AC max.                | 4 A    |
| Rated current DC max.                | 0.2 A  |
| Rated current AC/DC min.             | 5 mA   |
| Contact resistance acc. to life max. | 200 mΩ |
| Protection class                     | II     |
| ESD-strength min.                    | 14 kV  |

## Other specifications

|   |  |
|---|--|
| Operating life, at 250 V/2 A (operations)       | 200,000 (momentary) cycle                |
| Operating life, at 250 V/4 A (operations)       | 60,000 (momentary), 10,000 (latching)    |
| Degree of protection from front side            | IP40 (DIN EN 60529)                      |
| Operation temperature min.                      | -25 °C                                   |
| Ambient temp. operating max. without lamp / LED | +70 °C                                   |
| Ambient temp. operating max. with lamp /LED     | +55 °C                                   |
| Storage temperature min.                        | -40 °C                                   |
| Storage temperature max.                        | +80 °C                                   |
| Environmental resistance                        | acc. to IEC 60068-2-14, -30, -33 and -78 |
| Approvals                                       | ENEC 25 T 55 (70), UL, CSA               |
| Flame class acc. to UL 94                       | V 1                                      |
| Hot wire ignition acc. to IEC 60695-2-1         | yes                                      |
| ROHS compliant                                  | yes                                      |
| REACH compliant                                 | yes                                      |

## Panel cut-out



