

RAFIX 16 - Emergency stop pushbutton, round collar, conical, dupe-proof, non-blocking

1.30.074.281/0300

Only use universal contact blocks with momentary function.



The positively driven mechanical arrangement is dupe-proof to EN 418.

General information

| | |
|-------------------|------------|
| Actuator | mushroom |
| Color of mushroom | opaque red |
| Form of collar | round |

Dimensions

| | |
|-------------------|------------|
| Collar dimensions | ø 24.95 mm |
| Overall height | 29 mm |
| Mounting depth | 44.7 mm |
| Mounting hole | 16.2 mm |

Mechanical design

| | |
|---------------------|--|
| Mounting | ring nut |
| Contact function | latching |
| Contact arrangement | according to contact block |
| Illumination | no |
| Reset | counterclockwise or clockwise rotation |

Mechanical characteristics

| | |
|-----------------|-----------------------|
| Robustness max. | 100 N |
| Robustness | acc. to IEC 60947-5-5 |

Other specifications

| | |
|---|--|
| Operating life (operations) | 30,000 cycle |
| Degree of protection from front side | IP65 (DIN EN 60529) |
| Operation temperature min. | -25 °C |
| Ambient temp. operating max. without lamp / LED | +70 °C |
| Ambient temp. operating max. with lamp /LED | +55 °C |
| Storage temperature min. | -40 °C |
| Storage temperature max. | +85 °C |
| Environmental resistance | acc. to IEC 60068-2-14, -30, -33 and -78 |
| Corresponding to CE Ma-Dir. 89/392 | yes |
| ROHS compliant | yes |
| REACH compliant | yes |

Panel cut-out

