

RAFIX 16, lamp socket W2 x 4.6d, quick-connect terminal, for W 2 x 4.6d



fields of application

- › Measurement-control-regulation
- › Electrical engineering
- › Mechanical and system engineering
- › Industrial robots

special features

- › Lamp socket Wedge-Base W 2x4.6d for LED.
- › A notch on the lamp socket indicates the cathode side.
- › Mounting by snapping on or snapping into signal lamp
- › Flat terminals 2.8 x 0.8 mm



description

Lamp socket for snapping in or onto signal lamps.

technical data

› general

Color	light gray
Operating temperature, min.	-25 °C
Operating temperature, max.	55 °C
Storage temperature, min.	-40 °C
Storage temperature, max.	85 °C
illuminated	Yes
Lamp socket	W 2 x 4.6d
Packaging unit	5 pcs.
net weight	1.8 g
Environment resistance	IEC 60068-2-14 IEC 60068-2-30 IEC 60068-2-33 IEC 60068-2-78
Shock resistance according to standard IEC 60068-2-27	50 g at 11 ms amplitude semi-sinusoidal
Vibration-resistance according to standard IEC 60068-2-6	10 g at 20 - 500 Hz
MOQ order	10 pcs.
RoHS compliant	Yes
REACH compliant	Yes

› mounting diameters

Outside dimension, length	15.9 mm
Outside dimension, width	15.9 mm
Outside dimension, height	23.7 mm
Mounting depth	30.5 mm

direct links

- › [RAFI eCatalog](#)

> mechanical data

Fixing	Latching
Solderability	No
Terminal on the rear	Flat quick-connect terminal 2.8 x 0.8

drawings

System drawing