

Accessories - MCC 0,5-MP AU 0,14-0,5



1013425

<https://www.phoenixcontact.com/in/products/1013425>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Crimp contact, nominal current: 6 A, type of contact: Female connector, connection method: Crimp connection, contact surface: Gold, type of packaging: Bulk goods

Accessories - MCC 0,5-MP AU 0,14-0,5



1013425

<https://www.phoenixcontact.com/in/products/1013425>

Commercial Data

Item number	1013425
Packing unit	100 pc
Minimum order quantity	100 pc
Sales Key	AAA
Product Key	AAACAB
GTIN	4055626492414
Weight per Piece (including packing)	0.42 g
Weight per Piece (excluding packing)	0.064 g
Customs tariff number	85366990
Country of origin	DE

Accessories - MCC 0,5-MP AU 0,14-0,5



1013425

<https://www.phoenixcontact.com/in/products/1013425>

Technical Data

Product properties

Product type	Crimp contact
Pitch	0 mm

Material specifications

Contact surface	Gold Au
-----------------	---------

Dimensions

Pitch	0 mm
-------	------

Packaging specifications

Type of packaging	Bulk goods
-------------------	------------

Accessories - MCC 0,5-MP AU 0,14-0,5



1013425

<https://www.phoenixcontact.com/in/products/1013425>

Approvals



EAC

Approval ID: B.01687

Accessories - MCC 0,5-MP AU 0,14-0,5



1013425

<https://www.phoenixcontact.com/in/products/1013425>

Classifications

ECLASS

ECLASS-9.0	27440204
ECLASS-10.0.1	27440204
ECLASS-11.0	27460403

ETIM

ETIM 8.0	EC000796
----------	----------

UNSPSC

UNSPSC 21.0	39121500
-------------	----------

Accessories - MCC 0,5-MP AU 0,14-0,5



1013425

<https://www.phoenixcontact.com/in/products/1013425>

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

1013425

<https://www.phoenixcontact.com/in/products/1013425>

Accessories

PCB connector

PCB connector - MCC 0,5/ 2-ST-2,54 - 1012266

<https://www.phoenixcontact.com/in/products/1012266>



PCB connector, nominal cross section: 0.75 mm², color: black, nominal current: 6 A, rated voltage (III/2): 160 V, type of contact: Female connector, number of potentials: 2, number of rows: 1, number of positions: 2, number of connections: 2, product range: MCC 0,5/..-ST, pitch: 2.54 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, plug-in system: COMBICON FMC 0,5, locking: without, mounting: without, type of packaging: packed in cardboard

PCB connector

PCB connector - MCC 0,5/ 3-ST-2,54 - 1012267

<https://www.phoenixcontact.com/in/products/1012267>



PCB connector, nominal cross section: 0.75 mm², color: black, nominal current: 6 A, rated voltage (III/2): 160 V, type of contact: Female connector, number of potentials: 3, number of rows: 1, number of positions: 3, number of connections: 3, product range: MCC 0,5/..-ST, pitch: 2.54 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, plug-in system: COMBICON FMC 0,5, locking: without, mounting: without, type of packaging: packed in cardboard

1013425

<https://www.phoenixcontact.com/in/products/1013425>

PCB connector

PCB connector - MCC 0,5/ 4-ST-2,54 - 1012268

<https://www.phoenixcontact.com/in/products/1012268>



PCB connector, nominal cross section: 0.75 mm², color: black, nominal current: 6 A, rated voltage (III/2): 160 V, type of contact: Female connector, number of potentials: 4, number of rows: 1, number of positions: 4, number of connections: 4, product range: MCC 0,5/..-ST, pitch: 2.54 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, plug-in system: COMBICON FMC 0,5, locking: without, mounting: without, type of packaging: packed in cardboard

PCB connector

PCB connector - MCC 0,5/ 5-ST-2,54 - 1012269

<https://www.phoenixcontact.com/in/products/1012269>



PCB connector, nominal cross section: 0.75 mm², color: black, nominal current: 6 A, rated voltage (III/2): 160 V, type of contact: Female connector, number of potentials: 5, number of rows: 1, number of positions: 5, number of connections: 5, product range: MCC 0,5/..-ST, pitch: 2.54 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, plug-in system: COMBICON FMC 0,5, locking: without, mounting: without, type of packaging: packed in cardboard

1013425

<https://www.phoenixcontact.com/in/products/1013425>

PCB connector

PCB connector - MCC 0,5/ 6-ST-2,54 - 1012270

<https://www.phoenixcontact.com/in/products/1012270>



PCB connector, nominal cross section: 0.75 mm², color: black, nominal current: 6 A, rated voltage (III/2): 160 V, type of contact: Female connector, number of potentials: 6, number of rows: 1, number of positions: 6, number of connections: 6, product range: MCC 0,5/..-ST, pitch: 2.54 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, plug-in system: COMBICON FMC 0,5, locking: without, mounting: without, type of packaging: packed in cardboard

PCB connector

PCB connector - MCC 0,5/ 7-ST-2,54 - 1012271

<https://www.phoenixcontact.com/in/products/1012271>



PCB connector, nominal cross section: 0.75 mm², color: black, nominal current: 6 A, rated voltage (III/2): 160 V, type of contact: Female connector, number of potentials: 7, number of rows: 1, number of positions: 7, number of connections: 7, product range: MCC 0,5/..-ST, pitch: 2.54 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, plug-in system: COMBICON FMC 0,5, locking: without, mounting: without, type of packaging: packed in cardboard

1013425

<https://www.phoenixcontact.com/in/products/1013425>

PCB connector

PCB connector - MCC 0,5/ 8-ST-2,54 - 1012272

<https://www.phoenixcontact.com/in/products/1012272>



PCB connector, nominal cross section: 0.75 mm², color: black, nominal current: 6 A, rated voltage (III/2): 160 V, type of contact: Female connector, number of potentials: 8, number of rows: 1, number of positions: 8, number of connections: 8, product range: MCC 0,5/..-ST, pitch: 2.54 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, plug-in system: COMBICON FMC 0,5, locking: without, mounting: without, type of packaging: packed in cardboard

PCB connector

PCB connector - MCC 0,5/ 9-ST-2,54 - 1012273

<https://www.phoenixcontact.com/in/products/1012273>



PCB connector, nominal cross section: 0.75 mm², color: black, nominal current: 6 A, rated voltage (III/2): 160 V, type of contact: Female connector, number of potentials: 9, number of rows: 1, number of positions: 9, number of connections: 9, product range: MCC 0,5/..-ST, pitch: 2.54 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, plug-in system: COMBICON FMC 0,5, locking: without, mounting: without, type of packaging: packed in cardboard

1013425

<https://www.phoenixcontact.com/in/products/1013425>

PCB connector

PCB connector - MCC 0,5/10-ST-2,54 - 1012274

<https://www.phoenixcontact.com/in/products/1012274>



PCB connector, nominal cross section: 0.75 mm², color: black, nominal current: 6 A, rated voltage (III/2): 160 V, type of contact: Female connector, number of potentials: 10, number of rows: 1, number of positions: 10, number of connections: 10, product range: MCC 0,5/..-ST, pitch: 2.54 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, plug-in system: COMBICON FMC 0,5, locking: without, mounting: without, type of packaging: packed in cardboard

PCB connector

PCB connector - MCC 0,5/11-ST-2,54 - 1012276

<https://www.phoenixcontact.com/in/products/1012276>



PCB connector, nominal cross section: 0.75 mm², color: black, nominal current: 6 A, rated voltage (III/2): 160 V, type of contact: Female connector, number of potentials: 11, number of rows: 1, number of positions: 11, number of connections: 11, product range: MCC 0,5/..-ST, pitch: 2.54 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, plug-in system: COMBICON FMC 0,5, locking: without, mounting: without, type of packaging: packed in cardboard

1013425

<https://www.phoenixcontact.com/in/products/1013425>

PCB connector

PCB connector - MCC 0,5/12-ST-2,54 - 1012277

<https://www.phoenixcontact.com/in/products/1012277>



PCB connector, nominal cross section: 0.75 mm², color: black, nominal current: 6 A, rated voltage (III/2): 160 V, type of contact: Female connector, number of potentials: 12, number of rows: 1, number of positions: 12, number of connections: 12, product range: MCC 0,5/..-ST, pitch: 2.54 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, plug-in system: COMBICON FMC 0,5, locking: without, mounting: without, type of packaging: packed in cardboard

PCB connector

PCB connector - MCC 0,5/13-ST-2,54 - 1012278

<https://www.phoenixcontact.com/in/products/1012278>



PCB connector, nominal cross section: 0.75 mm², color: black, nominal current: 6 A, rated voltage (III/2): 160 V, type of contact: Female connector, number of potentials: 13, number of rows: 1, number of positions: 13, number of connections: 13, product range: MCC 0,5/..-ST, pitch: 2.54 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, plug-in system: COMBICON FMC 0,5, locking: without, mounting: without, type of packaging: packed in cardboard

1013425

<https://www.phoenixcontact.com/in/products/1013425>

PCB connector

PCB connector - MCC 0,5/14-ST-2,54 - 1012279

<https://www.phoenixcontact.com/in/products/1012279>



PCB connector, nominal cross section: 0.75 mm², color: black, nominal current: 6 A, rated voltage (III/2): 160 V, type of contact: Female connector, number of potentials: 14, number of rows: 1, number of positions: 14, number of connections: 14, product range: MCC 0,5/..-ST, pitch: 2.54 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, plug-in system: COMBICON FMC 0,5, locking: without, mounting: without, type of packaging: packed in cardboard

PCB connector

PCB connector - MCC 0,5/15-ST-2,54 - 1012281

<https://www.phoenixcontact.com/in/products/1012281>



PCB connector, nominal cross section: 0.75 mm², color: black, nominal current: 6 A, rated voltage (III/2): 160 V, type of contact: Female connector, number of potentials: 15, number of rows: 1, number of positions: 15, number of connections: 15, product range: MCC 0,5/..-ST, pitch: 2.54 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, plug-in system: COMBICON FMC 0,5, locking: without, mounting: without, type of packaging: packed in cardboard

1013425

<https://www.phoenixcontact.com/in/products/1013425>

PCB connector

PCB connector - MCC 0,5/16-ST-2,54 - 1012282

<https://www.phoenixcontact.com/in/products/1012282>



PCB connector, nominal cross section: 0.75 mm², color: black, nominal current: 6 A, rated voltage (III/2): 160 V, type of contact: Female connector, number of potentials: 16, number of rows: 1, number of positions: 16, number of connections: 16, product range: MCC 0,5/..-ST, pitch: 2.54 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, plug-in system: COMBICON FMC 0,5, locking: without, mounting: without, type of packaging: packed in cardboard

PCB connector

PCB connector - DMCC 0,5/ 2-ST-2,54 - 1027603

<https://www.phoenixcontact.com/in/products/1027603>



PCB connector, nominal cross section: 0.75 mm², color: black, nominal current: 6 A, rated voltage (III/2): 160 V, type of contact: Female connector, number of potentials: 4, number of rows: 2, number of positions: 2, number of connections: 4, product range: DMCC 0,5/..-ST, pitch: 2.54 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, plug-in system: COMBICON DFMC 0,5, locking: without, mounting: without, type of packaging: packed in cardboard

1013425

<https://www.phoenixcontact.com/in/products/1013425>

PCB connector

PCB connector - DMCC 0,5/ 3-ST-2,54 - 1027605

<https://www.phoenixcontact.com/in/products/1027605>



PCB connector, nominal cross section: 0.75 mm², color: black, nominal current: 6 A, rated voltage (III/2): 160 V, type of contact: Female connector, number of potentials: 6, number of rows: 2, number of positions: 3, number of connections: 6, product range: DMCC 0,5/..-ST, pitch: 2.54 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, plug-in system: COMBICON DFMC 0,5, locking: without, mounting: without, type of packaging: packed in cardboard

PCB connector

PCB connector - DMCC 0,5/ 4-ST-2,54 - 1027606

<https://www.phoenixcontact.com/in/products/1027606>



PCB connector, nominal cross section: 0.75 mm², color: black, nominal current: 6 A, rated voltage (III/2): 160 V, type of contact: Female connector, number of potentials: 8, number of rows: 2, number of positions: 4, number of connections: 8, product range: DMCC 0,5/..-ST, pitch: 2.54 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, plug-in system: COMBICON DFMC 0,5, locking: without, mounting: without, type of packaging: packed in cardboard

1013425

<https://www.phoenixcontact.com/in/products/1013425>

PCB connector

PCB connector - DMCC 0,5/ 5-ST-2,54 - 1027607

<https://www.phoenixcontact.com/in/products/1027607>



PCB connector, nominal cross section: 0.75 mm², color: black, nominal current: 6 A, rated voltage (III/2): 160 V, type of contact: Female connector, number of potentials: 10, number of rows: 2, number of positions: 5, number of connections: 10, product range: DMCC 0,5/..-ST, pitch: 2.54 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, plug-in system: COMBICON DFMC 0,5, locking: without, mounting: without, type of packaging: packed in cardboard

PCB connector

PCB connector - DMCC 0,5/ 6-ST-2,54 - 1027608

<https://www.phoenixcontact.com/in/products/1027608>



PCB connector, nominal cross section: 0.75 mm², color: black, nominal current: 6 A, rated voltage (III/2): 160 V, type of contact: Female connector, number of potentials: 12, number of rows: 2, number of positions: 6, number of connections: 12, product range: DMCC 0,5/..-ST, pitch: 2.54 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, plug-in system: COMBICON DFMC 0,5, locking: without, mounting: without, type of packaging: packed in cardboard

1013425

<https://www.phoenixcontact.com/in/products/1013425>

PCB connector

PCB connector - DMCC 0,5/ 7-ST-2,54 - 1027609

<https://www.phoenixcontact.com/in/products/1027609>



PCB connector, nominal cross section: 0.75 mm², color: black, nominal current: 6 A, rated voltage (III/2): 160 V, type of contact: Female connector, number of potentials: 14, number of rows: 2, number of positions: 7, number of connections: 14, product range: DMCC 0,5/..-ST, pitch: 2.54 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, plug-in system: COMBICON DFMC 0,5, locking: without, mounting: without, type of packaging: packed in cardboard

PCB connector

PCB connector - DMCC 0,5/ 8-ST-2,54 - 1027610

<https://www.phoenixcontact.com/in/products/1027610>



PCB connector, nominal cross section: 0.75 mm², color: black, nominal current: 6 A, rated voltage (III/2): 160 V, type of contact: Female connector, number of potentials: 16, number of rows: 2, number of positions: 8, number of connections: 16, product range: DMCC 0,5/..-ST, pitch: 2.54 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, plug-in system: COMBICON DFMC 0,5, locking: without, mounting: without, type of packaging: packed in cardboard

1013425

<https://www.phoenixcontact.com/in/products/1013425>

PCB connector

PCB connector - DMCC 0,5/ 9-ST-2,54 - 1027611

<https://www.phoenixcontact.com/in/products/1027611>



PCB connector, nominal cross section: 0.75 mm², color: black, nominal current: 6 A, rated voltage (III/2): 160 V, type of contact: Female connector, number of potentials: 18, number of rows: 2, number of positions: 9, number of connections: 18, product range: DMCC 0,5/..-ST, pitch: 2.54 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, plug-in system: COMBICON DFMC 0,5, locking: without, mounting: without, type of packaging: packed in cardboard

PCB connector

PCB connector - DMCC 0,5/10-ST-2,54 - 1027612

<https://www.phoenixcontact.com/in/products/1027612>



PCB connector, nominal cross section: 0.75 mm², color: black, nominal current: 6 A, rated voltage (III/2): 160 V, type of contact: Female connector, number of potentials: 20, number of rows: 2, number of positions: 10, number of connections: 20, product range: DMCC 0,5/..-ST, pitch: 2.54 mm, connection method: Crimp connection, conductor/PCB connection direction: 0 °, plug-in system: COMBICON DFMC 0,5, locking: without, mounting: without, type of packaging: packed in cardboard

1013425

<https://www.phoenixcontact.com/in/products/1013425>

PCB connector

PCB connector - DMCC 0,5/11-ST-2,54 - 1027613

<https://www.phoenixcontact.com/in/products/1027613>



PCB connector, nominal cross section: 0.75 mm^2 , color: black, nominal current: 6 A, rated voltage (III/2): 160 V, type of contact: Female connector, number of potentials: 22, number of rows: 2, number of positions: 11, number of connections: 22, product range: DMCC 0,5/..-ST, pitch: 2.54 mm, connection method: Crimp connection, conductor/PCB connection direction: 0° , plug-in system: COMBICON DFMC 0,5, locking: without, mounting: without, type of packaging: packed in cardboard

PCB connector

PCB connector - DMCC 0,5/12-ST-2,54 - 1027614

<https://www.phoenixcontact.com/in/products/1027614>



PCB connector, nominal cross section: 0.75 mm^2 , color: black, nominal current: 6 A, rated voltage (III/2): 160 V, type of contact: Female connector, number of potentials: 24, number of rows: 2, number of positions: 12, number of connections: 24, product range: DMCC 0,5/..-ST, pitch: 2.54 mm, connection method: Crimp connection, conductor/PCB connection direction: 0° , plug-in system: COMBICON DFMC 0,5, locking: without, mounting: without, type of packaging: packed in cardboard

1013425

<https://www.phoenixcontact.com/in/products/1013425>

PCB connector

PCB connector - DMCC 0,5/13-ST-2,54 - 1027615

<https://www.phoenixcontact.com/in/products/1027615>



PCB connector, nominal cross section: 0.75 mm^2 , color: black, nominal current: 6 A, rated voltage (III/2): 160 V, type of contact: Female connector, number of potentials: 26, number of rows: 2, number of positions: 13, number of connections: 26, product range: DMCC 0,5/..-ST, pitch: 2.54 mm, connection method: Crimp connection, conductor/PCB connection direction: 0° , plug-in system: COMBICON DFMC 0,5, locking: without, mounting: without, type of packaging: packed in cardboard

PCB connector

PCB connector - DMCC 0,5/14-ST-2,54 - 1027616

<https://www.phoenixcontact.com/in/products/1027616>



PCB connector, nominal cross section: 0.75 mm^2 , color: black, nominal current: 6 A, rated voltage (III/2): 160 V, type of contact: Female connector, number of potentials: 28, number of rows: 2, number of positions: 14, number of connections: 28, product range: DMCC 0,5/..-ST, pitch: 2.54 mm, connection method: Crimp connection, conductor/PCB connection direction: 0° , plug-in system: COMBICON DFMC 0,5, locking: without, mounting: without, type of packaging: packed in cardboard

1013425

<https://www.phoenixcontact.com/in/products/1013425>

PCB connector

PCB connector - DMCC 0,5/15-ST-2,54 - 1027617

<https://www.phoenixcontact.com/in/products/1027617>



PCB connector, nominal cross section: 0.75 mm^2 , color: black, nominal current: 6 A, rated voltage (III/2): 160 V, type of contact: Female connector, number of potentials: 30, number of rows: 2, number of positions: 15, number of connections: 30, product range: DMCC 0,5/..-ST, pitch: 2.54 mm, connection method: Crimp connection, conductor/PCB connection direction: 0° , plug-in system: COMBICON DFMC 0,5, locking: without, mounting: without, type of packaging: packed in cardboard

PCB connector

PCB connector - DMCC 0,5/16-ST-2,54 - 1027618

<https://www.phoenixcontact.com/in/products/1027618>



PCB connector, nominal cross section: 0.75 mm^2 , color: black, nominal current: 6 A, rated voltage (III/2): 160 V, type of contact: Female connector, number of potentials: 32, number of rows: 2, number of positions: 16, number of connections: 32, product range: DMCC 0,5/..-ST, pitch: 2.54 mm, connection method: Crimp connection, conductor/PCB connection direction: 0° , plug-in system: COMBICON DFMC 0,5, locking: without, mounting: without, type of packaging: packed in cardboard

Accessories - MCC 0,5-MP AU 0,14-0,5



1013425

<https://www.phoenixcontact.com/in/products/1013425>

Crimping pliers

Crimping pliers - CRIMPFOX-P CC 0.75 L - 1064998

<https://www.phoenixcontact.com/in/products/1064998>



Crimping pliers, for COMBICON crimp connectors with cross section: 0.14 ... 0.75 mm². Unlockable pressure lock, precise parallel crimping, front entry, B crimp, incl. 2 positioning aids

Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

info@phoenixcontact.co.in