

Conductor marker carrier - PATG HF 2/10



1014050

<https://www.phoenixcontact.com/us/products/1014050>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Conductor marker carrier, transparent/black, unlabeled, mounting type: slide-on, cable diameter range: 2 ... 4 mm, lettering field size: 10 x 4 mm

Your advantages

- The PATG HF... sleeve is a captive marker carrier
- These conductor marking systems consist of marker carriers and insert labels
- Comprehensive approvals ensure international use
- The use of high-quality plastics supports the most stringent demands of the rail industry and the automotive industry
- The corresponding UCT-WMT... and UC-WMT... insert labels are used for marking
- Due to the plastic properties of the PATG HF..., high-quality fluid printing of the UC-WMT... with the BLUEMARK... is required

Commercial Data

Item number	1014050
Packing unit	1 pc
Minimum order quantity	1,000 pc
Note	Made to Order (non-returnable)
Sales Key	B12
Product Key	BG221A
Catalog Page	Page 250 (C-3-2019)
GTIN	4046356779371
Weight per Piece (including packing)	0.222 g
Weight per Piece (excluding packing)	0.222 g
Customs tariff number	39269097
Country of origin	DE

1014050

<https://www.phoenixcontact.com/us/products/1014050>

Technical Data

Product properties

Product type	Marker carrier cable
Type	Profile

Dimensions

Width	6.1 mm
Length	10 mm

External dimensions

Outside diameter	2 mm ... 4 mm
------------------	---------------

Material specifications

Color	transparent/black
Material	TPU
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 2
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Components	free from silicone, halogen, and cadmium

Cable / line

External cable diameter	2 mm ... 4 mm
-------------------------	---------------

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

	VDMA 24364-A1-L:2018-05
Result	Test passed

UV resistance

Specification	ISO 4892-2:2013-03
Result	Test passed
Test duration	96 h

Temperature resistance

Specification	ANSI/UL 969-2018:03 (following)
Test duration	240 h
Rating 100 °C (121 °C)	Test passed
Specification	ISO 175:2010 (following)
Test duration	168 h

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S

Conductor marker carrier - PATG HF 2/10



1014050

<https://www.phoenixcontact.com/us/products/1014050>

Cycles	2
--------	---

Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed
Test duration	96 h

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
Recommended storage conditions	23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 %

Mounting

Mounting type	slide-on
---------------	----------

Conductor marker carrier - PATG HF 2/10



1014050

<https://www.phoenixcontact.com/us/products/1014050>

Classifications

ECLASS

ECLASS-9.0	27400401
ECLASS-10.0.1	27400401
ECLASS-11.0	27281105

ETIM

ETIM 8.0	EC001530
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

Conductor marker carrier - PATG HF 2/10



1014050

<https://www.phoenixcontact.com/us/products/1014050>

Accessories

Conductor marker

Conductor marker - UCT-WMT (10X4) - 0801430

<https://www.phoenixcontact.com/us/products/0801430>



Conductor marker, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: insert, cable diameter range: 0.6 ... 7 mm, lettering field size: 10 x 4 mm, Number of individual labels: 60

Conductor marker

Conductor marker - UCT-WMT (10X4) YE - 0801431

<https://www.phoenixcontact.com/us/products/0801431>



Conductor marker, Sheet, yellow, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: insert, cable diameter range: 0.6 ... 7 mm, lettering field size: 10 x 4 mm, Number of individual labels: 60

Conductor marker carrier - PATG HF 2/10

1014050

<https://www.phoenixcontact.com/us/products/1014050>

Conductor marker

Conductor marker - UCT-WMT (10X4) RD - 0801433

<https://www.phoenixcontact.com/us/products/0801433>



Conductor marker, Sheet, red, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: insert, cable diameter range: 0.6 ... 7 mm, lettering field size: 10 x 4 mm, Number of individual labels: 60

Conductor marker

Conductor marker - UCT-WMT (10X4) OG - 0801434

<https://www.phoenixcontact.com/us/products/0801434>



Conductor marker, Sheet, orange, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: insert, cable diameter range: 0.6 ... 7 mm, lettering field size: 10 x 4 mm, Number of individual labels: 60

Conductor marker carrier - PATG HF 2/10

1014050

<https://www.phoenixcontact.com/us/products/1014050>

Conductor marker

Conductor marker - UCT-WMT (10X4) GN - 0801435

<https://www.phoenixcontact.com/us/products/0801435>



Conductor marker, Sheet, green, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: insert, cable diameter range: 0.6 ... 7 mm, lettering field size: 10 x 4 mm, Number of individual labels: 60

Conductor marker

Conductor marker - UCT-WMT (10X4) VT - 0801436

<https://www.phoenixcontact.com/us/products/0801436>



Conductor marker, Sheet, violet, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: insert, cable diameter range: 0.6 ... 7 mm, lettering field size: 10 x 4 mm, Number of individual labels: 60

Conductor marker carrier - PATG HF 2/10

1014050

<https://www.phoenixcontact.com/us/products/1014050>

Conductor marker

Conductor marker - UCT-WMT (10X4) BU - 0801437

<https://www.phoenixcontact.com/us/products/0801437>



Conductor marker, Sheet, blue, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: insert, cable diameter range: 0.6 ... 7 mm, lettering field size: 10 x 4 mm, Number of individual labels: 60

Cable marker

Cable marker - UC-WMT (10X4) - 0819372

<https://www.phoenixcontact.com/us/products/0819372>



Cable marker, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: insert, cable diameter range: 0.6 ... 7 mm, lettering field size: 10 x 4 mm, Number of individual labels: 48

Conductor marker carrier - PATG HF 2/10

1014050

<https://www.phoenixcontact.com/us/products/1014050>

Cable marker

Cable marker - UC-WMT (10X4) YE - 0819385

<https://www.phoenixcontact.com/us/products/0819385>



Cable marker, Sheet, yellow, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: insert, cable diameter range: 0.6 ... 7 mm, lettering field size: 10 x 4 mm, Number of individual labels: 48

Cable marker

Cable marker - UC-WMT (10X4) BU - 0820992

<https://www.phoenixcontact.com/us/products/0820992>



Cable marker, Sheet, blue, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: insert, cable diameter range: 0.6 ... 7 mm, lettering field size: 10 x 4 mm, Number of individual labels: 48

Conductor marker carrier - PATG HF 2/10

1014050

<https://www.phoenixcontact.com/us/products/1014050>

Cable marker

Cable marker - UC-WMT (10X4) RD - 0821001

<https://www.phoenixcontact.com/us/products/0821001>



Cable marker, Sheet, red, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: insert, cable diameter range: 0.6 ... 7 mm, lettering field size: 10 x 4 mm, Number of individual labels: 48

Cable marker

Cable marker - UC-WMT (10X4) OG - 0823986

<https://www.phoenixcontact.com/us/products/0823986>



Cable marker, Sheet, orange, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: insert, cable diameter range: 0.6 ... 7 mm, lettering field size: 10 x 4 mm, Number of individual labels: 48

Conductor marker carrier - PATG HF 2/10

1014050

<https://www.phoenixcontact.com/us/products/1014050>

Cable marker

Cable marker - UC-WMT (10X4) GN - 0823999

<https://www.phoenixcontact.com/us/products/0823999>



Cable marker, Sheet, green, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: insert, cable diameter range: 0.6 ... 7 mm, lettering field size: 10 x 4 mm, Number of individual labels: 48

Cable marker

Cable marker - UC-WMT (10X4) VT - 0825360

<https://www.phoenixcontact.com/us/products/0825360>



Cable marker, Sheet, violet, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: insert, cable diameter range: 0.6 ... 7 mm, lettering field size: 10 x 4 mm, Number of individual labels: 48

Conductor marker carrier - PATG HF 2/10



1014050

<https://www.phoenixcontact.com/us/products/1014050>

Insert label

Insert label - MM-EMT (EX4)R C1 WH/BK - 1169312

<https://www.phoenixcontact.com/us/products/1169312>



Insert label, Roll, white/black, unlabeled, can be labeled with: THERMOFOX, THERMOMARK GO, THERMOMARK GO.K, mounting type: snapped, lettering field size: continuous x 3 mm

Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com