

Connector - ES-BPC-C 16-25 OG - 1106306

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




High-voltage connector for new energy storage system, rated voltage: 1500 V, rated current: 120 A; wiring method: crimping; surface coating: silver; negative pole: black; with one set of plug and socket each;

Your advantages

- ✓ Patented design with "three proofs and one rotation"
- ✓ Mismatching and short circuit proof
- ✓ Touch proof
- ✓ Foolproof mechanism installed
- ✓ Safety lock
- ✓ 360 degree free rotation and flexible wiring



Key Commercial Data

Packing unit	1 pc
GTIN	 4 063151 003470
GTIN	4063151003470
Weight per Piece (excluding packing)	36.000 g
Custom tariff number	85359000
Country of origin	China

Technical data

Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C
---------------------------------	-------------------

General

Nominal voltage U_N	1500 V
Degree of protection	IP65

Connector - ES-BPC-C 16-25 OG - 1106306

Technical data

Standards and Regulations

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 9.0	27062002
------------	----------