

## Connector - ES-BPC-C 16-25 BK - 1106307

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



High-voltage connector for new energy storage system, rated voltage: 1500 V, rated current: 120 A; wiring method: crimping; surface coating: silver; negative pole: black; with one set of plug and socket each;

### Your advantages

- Patented design with "three proofs and one rotation"
- Mismatching and short circuit proof
- Touch proof
- Foolproof mechanism installed
- Safety lock
- 360 degree free rotation and flexible wiring



### Key Commercial Data

Packing unit	1 pc
GTIN	
GTIN	4063151003456
Weight per Piece (excluding packing)	40.000 g
Custom tariff number	85359000
Country of origin	China

### Technical data

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C
---------------------------------	-------------------

#### General

Nominal voltage $U_N$	1500 V
Degree of protection	IP65

## Connector - ES-BPC-C 16-25 BK - 1106307

### Technical data

#### Standards and Regulations

#### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

### Classifications

#### eCl@ss

eCl@ss 9.0	27062002
------------	----------