

THM WO 24.5/62 WS**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Similar to illustration

THM WriteOn cable markers on reels are used for labelling conductors and cables with an outside diameter of up to 36 mm. The transparent adhesive strip fixes and protects the printing on the marker surface.

- Protection of the marking against dirt and abrasion by wrapping it with the transparent adhesive strip
- Simple and quick printing with the high-quality thermal transfer printers

General ordering data

| | |
|--------------------|--|
| Version | THM, Conductor and cable markers, 6.1 - 13.7 mm, 24.5 x 62 mm, white |
| Order No. | 1109130000 |
| Type | THM WO 24.5/62 WS |
| GTIN (EAN) | 4032248885534 |
| Qty. | 1 pc(s). |
| compatible printer | 2599430000 2599440000 |

Creation date May 18, 2023 11:23:03 AM CEST

Catalogue status 12.05.2023 / We reserve the right to make technical changes.

THM WO 24.5/62 WS

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|------------|----------|-----------------|------------|
| Depth | 0.025 mm | Depth (inches) | 0.001 inch |
| Height | 24.5 mm | Height (inches) | 0.965 inch |
| Width | 62 mm | Width (inches) | 2.441 inch |
| Net weight | 557 g | | |

Temperatures

| | |
|-----------------------------|--------------|
| Operating temperature range | -40...150 °C |
|-----------------------------|--------------|

General data

| | | | |
|-----------------------------------|--|--|-----------------|
| Adhesive | Polyacrylate adhesive | Approval acc. to UL 969 | Yes |
| Colour | white | Halogen | No |
| Material | Polyester film | Material colour according to resistance code | 9 |
| Number of markers per combination | 1 Label reel = Conductor and cable markers | Number per roll | 2,500 |
| Operating temperature range | -40...150 °C | Operating temperature range, max. | 150 °C |
| Operating temperature range, min. | -40 °C | Size of labelling field | 19.05 x 24.5 mm |
| Type of printing | neutral | UL 94 flammability rating | V-0 |
| Version | Self-adhesive | Width | 62 mm |

Conductor and cable markers

| | | | |
|-------------------------------|----------------------|----------------------------------|----------------------------|
| Conductor O.D. | 6.1 - 13.7 mm | Conductor O.D., max. | 13.7 mm |
| Conductor O.D., min. | 6.1 mm | Conductor cross-section, max. | 150 mm ² |
| Conductor cross-section, min. | 0.75 mm ² | Cross-section for connected wire | 0.75 - 150 mm ² |
| Halogen | No | Text field height | 19.05 mm |
| Text field width | 24.5 mm | | |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC001530 | ETIM 7.0 | EC001530 |
| ETIM 8.0 | EC001530 | ECLASS 9.0 | 27-40-04-01 |
| ECLASS 9.1 | 27-40-04-01 | ECLASS 10.0 | 27-40-04-01 |
| ECLASS 11.0 | 27-28-11-02 | ECLASS 12.0 | 27-28-11-02 |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|------------------|--|
| Engineering Data | CAD data – STEP |
| Engineering Data | WSCAD, Zuken E3.S, EPLAN |
| Catalogues | Catalogues in PDF-format |

Data sheet

THM WO 24.5/62 WS

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

