

**Accessories  
PS\_ZQV**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Current and voltage transformer wiring**

Our test disconnect terminal blocks featuring spring and screw connection technology allow you to create all the important converter circuits for measuring current, voltage and power in a safe and sophisticated way.

**General ordering data**

|            |                            |
|------------|----------------------------|
| Type       | PS_ZQV                     |
| Order No.  | <a href="#">1121740000</a> |
| Version    | Accessories, Test plug     |
| GTIN (EAN) | 4032248902675              |
| Qty.       | 1 pc(s).                   |

**Accessories**  
**PS\_ZQV**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data****Dimensions and weights**

|            |       |                 |            |
|------------|-------|-----------------|------------|
| Height     | 94 mm | Height (inches) | 3.701 inch |
| Net weight | 18 g  | Diameter        | 4 mm       |

**System specifications**

|         |           |               |      |
|---------|-----------|---------------|------|
| Version | Test plug | Mounting rail | none |
|---------|-----------|---------------|------|

**Additional technical data**

|                  |         |
|------------------|---------|
| Type of mounting | Plugged |
|------------------|---------|

**Conductors for clamping (rated connection)**

|                    |                    |
|--------------------|--------------------|
| Type of connection | Plug-in connection |
|--------------------|--------------------|

**Dimensions**

|          |      |
|----------|------|
| Diameter | 4 mm |
|----------|------|

**Rating data**

|               |         |  |         |
|---------------|---------|--|---------|
| Rated voltage | 1,000 V | Max. voltage of clamp support & pluggable system | 1,000 V |
| Rated current | 20 A    | Current at maximum wires                         | 20 A    |

**Classifications**

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 6.0   | EC002555    | eClass 6.2 | 27-20-92-02 |
| eClass 7.1 | 27-20-92-02 | eClass 8.1 | 27-14-11-48 |
| eClass 9.0 | 27-14-11-48 | eClass 9.1 | 27-14-11-48 |

**Product information**

|                                 |  |
|---------------------------------|--|
| Descriptive text ordering data  | 1x measuring probe red, 1x measuring probe black.        |
| Descriptive text technical data | For Feed-through terminals with a pitch of 3.5mm to 8mm. |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                    |   |
|--------------------|---|
| Brochure/Catalogue | <a href="#">CAT 6 TOOLS 15/16 EN</a><br><a href="#">CAT 1 TERM 16/17 EN</a> |
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>                                    |