

**Marking systems
THM-TWINMARK**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



The THM TwinMark printer is based on thermal transfer technology and has two separate printing heads. The two printing heads function independently and make it possible to print shrink sleeves on both sides. The printer offers outstanding printing quality and is suitable for TwinMark shrink sleeves on reels.

The user-friendly system is operated with the M-Print® PRO software.

- An LCD graphic display shows all important status information
- Automatic positioning with margin stops
- It is possible to print identical or different data on top and bottom sides.
- Operation with Weidmüller's M-Print® PRO software

General ordering data

Type	THM-TWINMARK
Order No.	1140490000
Version	Marking systems, Thermotransfer printer, Thermotransfer, 300 dpi, Shrink-fit sleeves
GTIN (EAN)	4032248922413
Qty.	1 pc(s).

Marking systems THM-TWINMARK

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Dimensions and weights

Width	248 mm	Width (inches)	9.764 inch
Height	554 mm	Height (inches)	21.811 inch
Depth	395 mm	Depth (inches)	15.551 inch
Weight	21 Kg	Net weight	21,000 Kg

Labelling systems

Included in delivery	THM TwinMark, Printer driver, Mains cable, Euro plug, UK plug, US plug, USB cable, Software M-Print® PRO, Manuals (CD), RIBBON MM 110/360 SW ink ribbon, Ink ribbon core	Interface	USB, Ethernet 10/100 Base T, LAN
Marker type	Shrink-fit sleeves	Operating system	Windows 7, Windows 8, Windows 8.1, Windows 10
Operation with rechargeable batteries	No	Print quality	300 dpi
Printer driver	Windows 7, Windows 8, Windows 8.1, Windows 10	Printing method	Thermotransfer
Printing speed	125 mm/s	Software	M-Print® PRO
Supply voltage	100...240 V AC	System requirements	PC with operating system Windows 7, 8 or 10
Type	THM TwinMark printer		

Classifications

ETIM 3.0	EC0006 10	ETIM 4.0	EC0006 10
ETIM 5.0	EC0006 10	ETIM 6.0	EC0006 10
UNSPSC	43-17-25-14	eClass 5.1	24-32-11-02
eClass 6.2	19-14-01-04	eClass 7.1	24-32-11-02
eClass 8.1	24-32-11-02	eClass 9.0	24-32-11-02
eClass 9.1	24-32-11-02		

Approvals

ROHS	Conform
------	---------

Downloads

Approval/Certificate/Document of Conformity	Konformitätserklärung 1140490000 DECLARATION OF CONFORMITY.pdf
---	--