

MTA 30 BK**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Due to the wide range of variants with output voltages of 5, 12, 24, and 48 V and extensive international approvals, they are suitable for use in many applications. The power range extends from 35 W to 350 W. The individual adaptability makes PRO-PM the right choice for many standard machines.

General ordering data

Version	Electronics housings, Mounting flange, Accessories
Order No.	1168970000
Type	MTA 30 BK
GTIN (EAN)	4032248960965
Qty.	45 pc(s).

Creation date January 13, 2023 2:33:36 PM CET

Catalogue status 09.01.2023 / We reserve the right to make technical changes.

MTA 30 BK

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	8 mm	Depth (inches)	0.315 inch
Height	67 mm	Height (inches)	2.638 inch
Width	30 mm	Width (inches)	1.181 inch
Length	68 mm	Length (inches)	2.677 inch
Net weight	20.089 g		

Temperatures

Operating temperature, min.	-50 °C	Operating temperature, max.	100 °C
-----------------------------	--------	-----------------------------	--------

General data

Weight	21.58 g
--------	---------

Classifications

ETIM 6.0	EC002625	ETIM 7.0	EC002625
ETIM 8.0	EC002625	ECLASS 9.0	27-18-28-07
ECLASS 9.1	27-04-92-90	ECLASS 10.0	27-18-28-07
ECLASS 11.0	27-18-28-07	ECLASS 12.0	27-18-28-07

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	CAD data – STEP
Catalogues	Catalogues in PDF-format
Brochures	FL ANALO.SIGN.CONV. EN MB DEVICE MANUF. EN FL MACHINE SAFETY EN FL 72H SAMPLE SER EN PO OMNIMATE EN FL 72H SAMPLE SER EN PO OMNIMATE EN

MTA 30 BK

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

