

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [1200845012](#)  
**Status:** **Active**  
**Overview:** Brad Ultra-Lock Connection System  
**Description:** Micro-Change (M12) Receptacle, 12 Poles, Female (Straight) to Leads, Front Panel Mount, 0.20m (7.87") Length

**Documents:**

[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

**Agency Certification**

CSA LR6837

**General**

Product Family Industrial Receptacles  
 Series [120084](#)  
 IP Rating IP69K  
 NEMA Rating NEMA 6  
 Overview [Brad Ultra-Lock Connection System](#)  
 Product Name Ultra-Lock (M12)  
 Type Single Ended (pigtail)  
 UPC 883906778187

**Physical**

Coupling Type Internal Thread  
 Gender Female  
 Keyway Single  
 Length 0.20m  
 Material - Component Nickel-plated Brass  
 Mounting Thread Size M16 x 1.5  
 Orientation Straight  
 Panel Mount Front  
 Poles 12  
 Temperature Range - Operating -25°C to +90°C  
 Wire Size AWG 26  
 Wire/Cable Type Leads, UL 1061

**Electrical**


Current - Maximum per Contact 1.5A  
 Voltage - Maximum 30V AC/DC

**Material Info**

Engineering Number WRCU20E01C200

**Reference - Drawing Numbers**

Sales Drawing 1200845013-000, 1200845107-000, SD-120084-142



*Series image - Reference only*

**EU ELV**

**Not Reviewed**

**EU RoHS**

**Not Reviewed**

**REACH SVHC**

Not Reviewed

**Halogen-Free**

**Status**

**Not Reviewed**

For more information, please visit [Contact US](#)

China ROHS

Not Reviewed

ELV

Not Reviewed

RoHS Phthalates

Not Reviewed

**Search Parts in this Series**

[120084 Series](#)