

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [120084-5013](#)  
**Status:** **Active**  
**Overview:** Brad® Ultra-Lock® Connection System  
**Description:** Micro-Change® (M12) Receptacle, Straight Female, Front Panel Mount, 12 Poles, Length 0.30m

**Documents:**

[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

**General**

Product Family	Industrial Receptacles
Series	<a href="#">120084</a>
IP Rating	IP69K
NEMA Rating	NEMA 6
Overview	<a href="#">Brad® Ultra-Lock® Connection System</a>
Product Name	Ultra-Lock® (M12)
Type	Single Ended (pigtail)
UPC	883906540807

**Physical**

Coupling Type	Internal Thread
Gender	Female
Keyway	Single
Length	0.30m
Material - Component	Nickel-plated Brass
Mounting Thread Size	M16 x 1.5
Net Weight	25.000/g
Orientation	Straight
Panel Mount	Front
Poles	12
Temperature Range - Operating	-25°C to +90°C
Wire Size AWG	26
Wire/Cable Type	Leads, UL 1061

**Electrical**

Current - Maximum per Contact	1.5A
Voltage - Maximum	30V AC/DC

**Material Info**

Old Part Number	WRCU20E01C300
-----------------	---------------

**Reference - Drawing Numbers**

Sales Drawing	SD-120084-142
---------------	---------------



**EU RoHS**

**RoHS Compliant by Exemption**  
**REACH SVHC**  
**Contains SVHC: No**  
**Low-Halogen Status**  
**Not Low-Halogen**

**China RoHS**



**Need more information on product environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
 For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

**Search Parts in this Series**

[120084Series](#)