

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [1201080314](#)  
**Status:** **Active**  
**Description:** Double-Ended RJ-45 Cordset, 4 Poles, Male (Straight) to Male (Straight), 26 AWG, Shielded TPE Cable, 2.0m (6.56' ) Length, 6.00mm (.236") Diameter, Teal

**Documents:**

[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

**Agency Certification**

UL E361772

**General**

|                      |                        |
|----------------------|------------------------|
| Product Family       | Industrial Cordsets    |
| Series               | <a href="#">120108</a> |
| Connector End A      | RJ-45 (standard)       |
| Connector End B      | RJ-45 (standard)       |
| IP Rating            | IP20                   |
| Material - Contact   | Copper Alloy           |
| Performance Category | 5e                     |
| Product Name         | Industrial Ethernet    |
| Protocol             | N/A                    |
| Type                 | Double Ended           |
| UPC                  | 78172541590            |

**Physical**

|                               |                      |
|-------------------------------|----------------------|
| Cable Diameter                | 6.00mm (.236")       |
| Cable Length                  | 2.0m (6.56')         |
| Color - Cable Jacket          | Teal                 |
| Coupling Style                | N/A                  |
| Gender                        | Male-Male            |
| Keyway                        | N/A                  |
| LED Indicator                 | No                   |
| Material - Cable Jacket       | TPE                  |
| Material - Connector Body     | PVC                  |
| Material - Coupling Nut       | N/A                  |
| Material - Plating Mating     | Gold                 |
| Net Weight                    | 119.294/g            |
| Orientation                   | Straight to Straight |
| Poles                         | 4                    |
| Temperature Range - Operating | -20°C to +75°C       |
| Wire Size AWG                 | 26                   |
| Wire/Cable Type               | Shielded TPE         |

**Electrical**

|                               |      |
|-------------------------------|------|
| Current - Maximum per Contact | 1.5A |
| Voltage - Maximum             | 30V  |

**Material Info**

|                    |               |
|--------------------|---------------|
| Engineering Number | E66A06005M020 |
|--------------------|---------------|

**Reference - Drawing Numbers**

|               |               |
|---------------|---------------|
| Sales Drawing | SD-120108-079 |
|---------------|---------------|



**EU ELV**

**Not Relevant**

**EU RoHS**

**Not Reviewed**

**REACH SVHC**

Not Reviewed

**Halogen-Free**

**Status**

**Not Reviewed**

For more information, please visit [Contact US](#)

China ROHS

Not Reviewed

ELV

Not Relevant

RoHS Phthalates

Not Reviewed

**Search Parts in this Series**

[120108 Series](#)