

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [121036-0295](#)  
**Status:** **Active**  
**Overview:** Brad® Ethernet Solutions  
**Description:** Micro-Change® (M12) to Brad® mPm® DIN Double-Ended Cordset, 5 Poles, Male (Straight) to DIN C, 0.60m Length, D-Coded Keyway

**Documents:**

[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

**General**

|                 |                                          |
|-----------------|------------------------------------------|
| Product Family  | Industrial Cordsets                      |
| Series          | <a href="#">121036</a>                   |
| Connector End A | Brad® mPm® DIN C                         |
| Connector End B | Micro-Change® (M12)                      |
| IP Rating       | IP65                                     |
| Overview        | <a href="#">Brad® Ethernet Solutions</a> |
| Product Name    | Micro-Change® (M12), mPm®                |
| Type            | Double Ended                             |
| UPC             | 883906223533                             |

**Physical**

|                               |                     |
|-------------------------------|---------------------|
| Cable Diameter                | 5.72mm (.225")      |
| Cable Length                  | 0.60m               |
| Color - Cable Jacket          | Black               |
| Coupling Style                | Threaded            |
| Gender                        | Male-Male           |
| Keyway                        | Single              |
| LED Indicator                 | Yes                 |
| Material - Cable Jacket       | PUR                 |
| Material - Connector Body     | PUR                 |
| Material - Contact            | Copper              |
| Material - Coupling Nut       | Nickel-plated Brass |
| Material - Plating Mating     | Gold over Nickel    |
| Net Weight                    | 30.000/g            |
| Orientation                   | Straight            |
| Poles                         | 5                   |
| Temperature Range - Operating | -25°C to +75°C      |
| Wire Size AWG                 | 22                  |
| Wire/Cable Type               | Shielded PUR        |

**Electrical**

|                               |      |
|-------------------------------|------|
| Current - Maximum per Contact | 1.5A |
| Voltage - Maximum             | 24V  |

**Material Info**

|                 |               |
|-----------------|---------------|
| Old Part Number | H850B0P12M006 |
|-----------------|---------------|

**Reference - Drawing Numbers**

|               |               |
|---------------|---------------|
| Sales Drawing | SD-121036-004 |
|---------------|---------------|

**EU RoHS**  
**ELV and RoHS**  
**Compliant**  
**REACH SVHC**  
**Not Reviewed**  
**Low-Halogen Status**  
**Not Reviewed**

**China RoHS**



**Need more information on product environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
 For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

**Search Parts in this Series**

[121036Series](#)