

Crimping pliers - CRIMPFOX-TC 4 - 1212113


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Crimping pliers, for CK 1,6-ED..., CK 2,5-ED..., CK 4,0-ED... turned contacts, 4 marked die stations, unlockable pressure lock, lateral entry, incl. positioning tool

Why buy this product

- Marked die stations for precise processing of corresponding cross sections
- Crimping pliers for processing turned contacts
- The integrated positioning tool ensures that the contacts are perfectly aligned in the die



Key Commercial Data

| | |
|--------------|---|
| Packing unit | 1 STK |
| GTIN |  4 046356 454018 |
| GTIN | 4046356454018 |

Technical data

Dimensions

| | |
|------------|--------|
| Length (b) | 256 mm |
| Width (a) | 25 mm |
| Height (c) | 68 mm |

General

| | |
|--------------------|----------------------|
| Color | black |
| Compression | Square crimp |
| Type of contact | Turned contacts |
| Designation | Crimping position 1 |
| Min. cross section | 0.14 mm ² |
| Max. cross section | 1 mm ² |
| AWG min | 26 |
| AWG max | 18 |

Crimping pliers - CRIMPFOX-TC 4 - 1212113

Technical data

General

| | |
|--------------------|----------------------|
| Designation | Crimping position 2 |
| Max. cross section | 1.5 mm ² |
| AWG max | 16 |
| Designation | Crimping position 3 |
| Max. cross section | 2.5 mm ² |
| AWG max | 14 |
| Die station | Crimping position 4 |
| Max. cross section | 4 mm ² |
| AWG max | 12 |
| Weight | 638 g |
| Min. cross section | 0.14 mm ² |
| Max. cross section | 4 mm ² |

Approvals


Approvals

Approvals

EAC

Ex Approvals

Approval details

| | | |
|-----|---|--------------------------|
| EAC |  | RU x- DE.xx08.B.02974 |
|-----|---|--------------------------|

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>