


**cable lug, terminal end
HBT 6,0 - 4,6 GE**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



The use of insulated connectors guarantees users a permanent and consistent quality for their electrical connections.
 In addition, they bring advantages during installation.

General ordering data

Type	HBT 6,0 - 4,6 GE
Order No.	1216230000
Version	cable lug, terminal end, Insulated cable connector, 4 mm ² - 6 mm ² , Yellow
GTIN (EAN)	4050118000337
Qty.	100 pc(s).

Data sheet

cable lug, terminal end HBT 6,0 - 4,6 GE

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Net weight	1.825 g	Insulation cross-section	6.4 mm
------------	---------	--------------------------	--------

Connectors

Conductor cross-section, max.	6 mm ²	Conductor cross-section, min.	4 mm ²
-------------------------------	-------------------	-------------------------------	-------------------

Dimensions

Hook nose X	2.8 mm	Insulation cross-section	6.4 mm
Length L	30.2 mm	Pin length P	17.2 mm
Pin width B	4.6 mm		

Classifications

ETIM 5.0	EC001059	ETIM 6.0	EC001059
eClass 6.2	27-40-02-01	eClass 7.1	27-40-02-04
eClass 8.1	27-40-02-12	eClass 9.0	27-40-02-12
eClass 9.1	27-40-02-12		

Approvals

ROHS	Conform
------	---------

Downloads

Brochure/Catalogue	CAT 6 TOOLS 15/16 EN CAT 1 TERM 16/17 EN
--------------------	---