



+ TERMINALS & SPLICES

PCB TERMINALS



✓ Active

TE CONNECTIVITY (TE)

TAB, POKE IN PCB 020 TPCUBR

Magnet Wire Terminals & Splices | MAG-MATE

1217041-1

TE Internal Number: 1217041-1

EU RoHS Compliant

EU ELV Compliant

Terminal Type Tab

PCB Thickness (Recommended) 1.57 mm [.062 in]

Mating Tab Width 4.75 mm [.187 in]

Mating Tab Thickness .51 mm [.02 in]

PCB Hole Diameter 1.32 mm [.052 in]

[↓ PRODUCT DRAWING](#)
English

[↓ 3D PDF](#)

DOCUMENTATION

Product Drawings

TAB, POK-IN, P.C.BOARD MOUNTED

PDF (TIFF AVAILABLE)

English

CAD Files

3D PDF

PDF

3D

Customer View Model

2D_DXF.ZIP

English

Customer View Model

3D_IGS.ZIP

English

Customer View Model

3D_STP.ZIP

English

Product Specifications

Application Specification

FASTON 110, 187, 205, 250, And 312 Series Tab Contacts For Printed Circuit (PC) Board Applications

PDF

English

Product Environmental Compliance

TE Material Declaration

MD_1217041-1_050620152228_dmtec

PDF

English

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

Terminates To Printed Circuit Board

Insulated Wire Support Yes

Configuration Features

Stud Hole No

Terminal Angle Straight

Body Features

Plating Material Tin

Plating Thickness (µin) 150

Contact Features

Terminal Type Tab

Contact Plating Material Tin

Dimensions

PCB Thickness (Recommended) 1.57 mm [.062 in]

Mating Tab Width 4.75 mm [.187 in]

Mating Tab Thickness .51 mm [.02 in]

PCB Hole Diameter 1.32 mm [.052 in]

Receptacle Stock Thickness .51 mm [.02 in]

Packaging Features

Packaging Method Package

Packaging Quantity 1000

Other

Comment Insertion equipment available.

PRODUCT COMPLIANCE



Statement of Compliance

Statement of Compliance

PDF
