

## Specification Sheet

Part Number: 126-02600



1-Piece Cable Tie/Arrowhead Mount with Wings in the Strap, 8.0" L, Hole Dia .24" - .26", PA66HS, Black, 1000/pkg

<b>Article Number</b>	126-02600
<b>Type</b>	T80RSF6.5F
<b>Color</b>	Black (BK)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• Arrowhead design is quick and easy to install by hand without the need for a tool.</li><li>• Ties "clicks" into place upon final installation signaling installer insertion is complete.</li><li>• Design provides low insertion and high extraction force.</li></ul>
<b>Quantity Per</b>	pcs.

<b>Product Description</b>	Arrowhead Push Ties secure fast and easy, while providing a disc feature to minimize the ingress of dust, dirt, and water. The anchor slides along the tie and adjusts for variations in panel thicknesses which insures a secure fixing at all times.
<b>Short Description</b>	1-Piece Cable Tie/Arrowhead Mount with Wings in the Strap, 8.0" L, Hole Dia .24" - .26", PA66HS, Black, 1000/pkg
<b>Global Part Name</b>	T80RSF6.5F-PA66HS-BK
<b>Minimum Tensile Strength (Imperial)</b>	80.0
<b>Minimum Tensile Strength (Metric)</b>	355
<b>Length L (Imperial)</b>	8.0
<b>Length L (Metric)</b>	209
<b>Fixation Method</b>	Arrowhead
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.18
<b>Width W (Metric)</b>	4.7

<b>Bundle Diameter Max (Imperial)</b>	1.97
<b>Bundle Diameter Max (Metric)</b>	50.0
<b>Thickness T (Metric)</b>	1.3
<b>Height H (Imperial)</b>	0.05
<b>Height H (Metric)</b>	1.3
<b>Panel Thickness Min(Imperial)</b>	0.02
<b>Panel Thickness Max(Imperial)</b>	0.02
<b>Panel Thickness Min (Metric)</b>	0.6
<b>Panel Thickness Max (Metric)</b>	3.0
<b>Mounting Hole Diameter D (Imperial)</b>	0.24 - 0.26
<b>Mounting Hole Diameter D (Metric)</b>	6.3 - 6.5 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.248
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.26
<b>Mounting Hole Diameter D Max (Metric)</b>	6.5

**Material**

Polyamide 6.6 heat stabilized (PA66HS)

<b>Material Shortcut</b>	PA66HS
<b>Operating Temperature (Metric)</b>	-40°F to +221°F (-40°C to +105°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	1000
<b>Package Quantity (Metric)</b>	1000
<b>Customs Number</b>	3926909988
<b>Content Unit(BMEcat)</b>	pcs.
<b>Weight (Metric)</b>	1.96