



**STRIPPING DIMENSIONS**

Directive 2002/95/EC RoHS compliant

(b)

**NOTES:**

- 1. MATERIAL: COPPER ALLOY
- 2. PLATING:
  - ITEM 1: SEE TABLE
  - ITEM 2: GOLD FLASH over NICKEL
  - ITEM 3: NICKEL PLATED
- 3. CRIMPING: USE CRIMP TOOL 360X10409X WITH TOOL INSERT 360X20029X  
SELECTOR SETTINGS: 7 FOR AWG 8  
6 FOR AWG 10

(b)

PLATING ITEM 1	PART-NO.
GOLD FLASH over NICKEL	132A11049X
min. 30µin HARD GOLD over min. 50µin NICKEL	132C11049X
min. 50µin HARD GOLD over min. 50µin NICKEL	132J11049X

(b)

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH

DO NOT ALTER CAD DRAWING BY HAND

finish SEE NOTES				tolerance ISO 2768-m		dim. in mm	
date				name		scale: 5:1	
drawn 23.03.98				Barcinski		material: SEE NOTES	
appd. 23.03.98				Mickenbecker		title: <b>HIGH POWER CONTACT FEMALE</b> CRIMP VERSION 40A D-SUB COMBINATION	
norm						dwg no:	
d-old						DIN-A4	
4 x b	Ä3854	19.01.11	K.H.	<b>CONEC</b> <sup>®</sup>			
a	Origin						
rev.	description	date	name				

part no:		SEE TABLE
dwg no:		13K11F0A
sh:		1

