

1370P Coax - System Integrators Video Cable



For more Information
please call

1-800-Belden1



Description:

20 AWG solid .032" bare copper conductor, plenum, foam FEP insulation, Duobond® II + tinned copper braid shield (85% coverage), Flam arrest® jacket.

Usage (Overall)

Suitable Applications: Commercial Video

Physical Characteristics (Overall)

Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
1	20	Solid	BC - Bare Copper	.032

Insulation

Insulation Material:

Insulation Trade Name	Insulation Material	Dia. (in.)
Teflon®	FFEP - Foam Fluorinated Ethylene Propylene	.133

Outer Shield

Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Duobond® II	Tape	Bonded Aluminum Foil-Polyester Tape-Aluminum Foil	100.000
2		Braid	TC - Tinned Copper	85.000

Outer Jacket

Outer Jacket Material:

Outer Jacket Trade Name	Outer Jacket Material
Flam arrest®	PVC - Polyvinyl Chloride

Overall Cable

Overall Nominal Diameter: 0.192 in.

Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +75°C

UL Temperature Rating: 75°C

Bulk Cable Weight: 24 lbs/1000 ft.

Max. Recommended Pulling Tension: 46 lbs.

Min. Bend Radius (Install)/Minor Axis: 2 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMP

CEC/C(UL) Specification: CMP

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy):	11/21/2011
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
RG Type:	59/U

Flame Test

UL Flame Test:	NFPA 262
----------------	----------

Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	No

Plenum/Non-Plenum

Plenum (Y/N):	Yes
Non-Plenum Number:	1370R

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)

75

Nom. Inductance:

Inductance (µH/ft)

0.097

Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)

16.1

Nominal Velocity of Propagation:

VP (%)

84

Nominal Delay:

Delay (ns/ft)

1.21

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

10.100

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

4.100

Nom. Attenuation:

Freq. (MHz) Attenuation (dB/100 ft.)

1	.29
3.58	.62
5	.70
7	.82
10	1.05
67.5	2.20
71.5	2.25
100	2.70
135	3.20
143	3.25
180	3.65
270	4.55

1370P Coax - System Integrators Video Cable

360	5.25
540	6.4
720	7.3
750	7.5
1000	9.4
1500	12.8
2250	17.5
3000	21.9

Max. Operating Voltage - UL:

Voltage
300 V RMS

Other Electrical Characteristic 1: Impedance tested in accordance with ASTM D-4566 paragraph 48.2, option 2 using a 75 Ohm fixed bridge and termination.

Other Electrical Characteristic 2: Return Loss tested in accordance with ASTM D-4566 paragraph 50.3, using a 75 Ohm fixed bridge and termination.

Minimum Return Loss:

Start Freq. (MHz)	Stop Freq. (MHz)	Min. RL (dB)
5.000	3000.000	15.000

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1370P N3U1000	1,000 FT	26.000 LB	GREEN, MIL		#20 FFEP SH FLRST
1370P N3U500	500 FT	13.500 LB	GREEN, MIL		#20 FFEP SH FLRST
1370P 0011000	1,000 FT	26.000 LB	BROWN		#20 FFEP SH FLRST
1370P 001500	500 FT	13.500 LB	BROWN		#20 FFEP SH FLRST
1370P 0021000	1,000 FT	26.000 LB	RED		#20 FFEP SH FLRST
1370P 002500	500 FT	13.500 LB	RED		#20 FFEP SH FLRST
1370P 0031000	1,000 FT	26.000 LB	ORANGE		#20 FFEP SH FLRST
1370P 003500	500 FT	13.500 LB	ORANGE		#20 FFEP SH FLRST
1370P 0041000	1,000 FT	26.000 LB	YELLOW		#20 FFEP SH FLRST
1370P 004500	500 FT	13.500 LB	YELLOW		#20 FFEP SH FLRST
1370P 0061000	1,000 FT	26.000 LB	BLUE, LIGHT		#20 FFEP SH FLRST
1370P 006500	500 FT	13.500 LB	BLUE, LIGHT		#20 FFEP SH FLRST
1370P 0071000	1,000 FT	26.000 LB	VIOLET		#20 FFEP SH FLRST
1370P 007500	500 FT	13.500 LB	VIOLET		#20 FFEP SH FLRST
1370P 0081000	1,000 FT	26.000 LB	GRAY		#20 FFEP SH FLRST
1370P 008500	500 FT	13.500 LB	GRAY		#20 FFEP SH FLRST
1370P 0091000	1,000 FT	26.000 LB	WHITE		#20 FFEP SH FLRST
1370P 009500	500 FT	13.500 LB	WHITE		#20 FFEP SH FLRST
1370P 0101000	1,000 FT	26.000 LB	BLACK		#20 FFEP SH FLRST
1370P 010500	500 FT	13.500 LB	BLACK		#20 FFEP SH FLRST

Revision Number: 2 Revision Date: 05-31-2012

© 2012 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

1370P Coax - System Integrators Video Cable

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.