

# Data cable - SAC-6P-100,0-970



1404174

<https://www.phoenixcontact.com/us/products/1404174>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



By the meter, Data cable, VARAN CAT5 (100 Mbps), shielded, SANTOPRENE halogen-free/TPE halogen-free, black RAL 9005, 6-wire (1x2xAWG22/19 + 1x4xAWG24/19), color single wire: Brown, blue, white/orange, white/green, green, orange, cable length: 100 m

## Commercial Data

Item number	1404174
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to Order (non-returnable)
Sales Key	B06
Product Key	BF1LEA
GTIN	4046356681711
Weight per Piece (including packing)	7,760 g
Weight per Piece (excluding packing)	7,760 g
Customs tariff number	85444995
Country of origin	DE

# Data cable - SAC-6P-100,0-970

1404174

<https://www.phoenixcontact.com/us/products/1404174>

## Technical Data

### Product properties

Product type	Data cable by the meter
Number of positions	6

### Electrical properties

Transmission medium	Copper
---------------------	--------


### Interfaces

Bus system	VARAN
Signal type/category	VARAN CAT5 (IEC 11801:2002)

### Cable / line

Cable length	100 m
--------------	-------

### VARAN [970]

Dimensional drawing	
Cable weight	81 kg/km
Number of positions	6
Shielded	yes
Cable type	VARAN [970]
Conductor structure	1x2xAWG22/19 + 1x4xAWG24/19
Conductor structure signal line	19x 0.13 mm
AWG signal line	24
Conductor cross section	4x 0.25 mm <sup>2</sup> (Signal line) 2x 0.38 mm <sup>2</sup> (Power supply)
Wire diameter incl. insulation	1.35 mm (Signal line) 1.5 mm (Power supply)
External cable diameter	7.8 mm ±0.2 mm
Outer sheath, material	SANTOPRENE halogen-free
External sheath, color	black RAL 9005
Conductor material	Bare Cu litz wires
Material wire insulation	PP
Single wire, color	Brown, blue, white/orange, white/green, green, orange
Type of pair shielding	Tinned copper braided shield, 95 % covering
Overall twist	1 star quad and 2 wires with 2 fillers

# Data cable - SAC-6P-100,0-970



1404174

<https://www.phoenixcontact.com/us/products/1404174>

Max. conductor resistance	77 $\Omega$ /m (Data cable)
Insulation resistance	5 G $\Omega$ *km (Data cable)
Wave impedance	100 $\Omega$ $\pm$ 15 %
Working capacitance	50 nF (Data cable)
Nominal voltage, cable	125 V (Data cable) 48 V (Power supply)
Test voltage	2000 V (Power supply) max. 700 V AC (Data cable)
Smallest bending radius, fixed installation	$\geq$ 93 mm
Smallest bending radius, movable installation	$\geq$ 93 mm
Max. bending cycles	3000000
Halogen-free	in accordance with DIN EN 50267-2-1
Ambient temperature (operation)	-20 °C ... 80 °C (Cable)
Ambient temperature (installation)	0 °C ... 50 °C

## Environmental and real-life conditions

### Ambient conditions

Ambient temperature (operation)	0 °C ... 50 °C (for installation) -20 °C ... 80 °C (cable, fixed installation)
---------------------------------	---

# Data cable - SAC-6P-100,0-970



1404174

<https://www.phoenixcontact.com/us/products/1404174>

## Classifications

### ECLASS

ECLASS-9.0	27061801
ECLASS-10.0.1	27061801
ECLASS-11.0	27061801
ECLASS-12.0	27061801

### ETIM

ETIM 8.0	EC003249
----------	----------

### UNSPSC

UNSPSC 21.0	26121600
-------------	----------

# Data cable - SAC-6P-100,0-970



1404174

<https://www.phoenixcontact.com/us/products/1404174>

## Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)