

# Network cable - NBC-M 8MS/ 1,0-93B



1407344

<https://www.phoenixcontact.com/us/products/1407344>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Network cable, Ethernet (100 Mbps), PROFINET (100 Mbps), EtherCAT® (100 Mbps), 4-position, shielded, Plug straight M8 / IP67, coding: A, on free cable end, cable length: 1 m

## Commercial Data

Item number	1407344
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to Order (non-returnable)
Sales Key	B06
Product Key	BF1BJI
Catalog Page	Page 394 (C-2-2019)
GTIN	4046356774628
Weight per Piece (including packing)	83.9 g
Weight per Piece (excluding packing)	82 g
Customs tariff number	85444290
Country of origin	PL

# Network cable - NBC-M 8MS/ 1,0-93B



1407344

<https://www.phoenixcontact.com/us/products/1407344>

## Technical Data

### Notes

General	Further products with variable cable type and variable cable length can be found in the accessories section
---------	---

### Product properties

Product type	Data cable preassembled
Number of positions	4
Application	Standard
No. of cable outlets	1
Shielded	yes
Coding	A - standard

### Interfaces

Bus system	Ethernet
Signal type/category	Ethernet, 100 Mbps
	PROFINET, 100 Mbps
	EtherCAT <sup>®</sup> , 100 Mbps
	Ethernet, 100 Mbps
	PROFINET, 100 Mbps
	EtherCAT <sup>®</sup> , 100 Mbps
	Ethernet, 100 Mbps
	PROFINET, 100 Mbps
	EtherCAT <sup>®</sup> , 100 Mbps

### LED signaling

Status display	No
Status display present	No

### Electrical properties

Nominal voltage $U_N$	30 V AC
	30 V DC
Nominal current $I_N$	4 A
Transmission medium	Copper

### Material specifications

Color Handle area	black
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuSn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Cable gland material	Zinc die-cast, nickel-plated

# Network cable - NBC-M 8MS/ 1,0-93B



1407344

<https://www.phoenixcontact.com/us/products/1407344>

## Connector

### Connection 1

Type	Plug straight M8 / IP67
Number of positions	4
Coding type	A (Standard)
Handle color	black
Material	CuSn (Contact) Ni/Au (Contact surface) TPU GF (Contact carriers) TPU, hardly inflammable, self-extinguishing (Grip) Zinc die-cast, nickel-plated (Screw connection)
Insertion/withdrawal cycles	≥ 100
Contact resistance	≤ 5 mΩ
Insulation resistance	≥ 100 MΩ
Tightening torque	0.2 Nm
Degree of protection	IP67
Ambient temperature (operation)	-25 °C ... 90 °C

### Connection 2

Type	free cable end
------	----------------

## Cable / line

Cable length	1 m
Cable weight	67 kg/km
UL AWM Style	21694
Number of positions	4
Shielded	yes
Cable type	PROFINET PVC stranded CAT5 [93B]
Signal runtime	5.3 ns/m
Signal speed	0.66 c
Conductor structure signal line	7x 0.25 mm
AWG signal line	22
Conductor cross section	4x 0.34 mm <sup>2</sup>
Wire diameter incl. insulation	1.55 mm
External cable diameter	6.5 mm ±0.2 mm
Outer sheath, material	PVC
External sheath, color	green RAL 6018
Conductor material	Tin-plated Cu litz wires
Material wire insulation	PE
Single wire, color	White, yellow, blue, orange
Thickness, outer sheath	approx. 0.9 mm
Overall twist	Star quad
Optical shield covering	85 %

# Network cable - NBC-M 8MS/ 1,0-93B



1407344

<https://www.phoenixcontact.com/us/products/1407344>

Insulation resistance	≥ 500 MΩ*km
Coupling resistance	≤ 20.00 mΩ/m (at 10 MHz)
Loop resistance	≤ 120.00 Ω/km
Wave impedance	100 Ω ±15 Ω (at 100 MHz)
Nominal voltage, cable	600 V
Test voltage Core/Core	2000 V (50 Hz, 1 min.)
Test voltage Core/Shield	2000 V (50 Hz, 1 min.)
Minimum bending radius, fixed installation	3 x D
Minimum bending radius, flexible installation	7 x D
Near end crosstalk attenuation (NEXT)	80 dB (with 1 MHz)
	76 dB (at 4 MHz)
	70 dB (at 10 MHz)
	65 dB (at 16 MHz)
	63 dB (at 20 MHz)
	60 dB (at 31.25 MHz)
	55 dB (at 62.5 MHz)
	50 dB (at 100 MHz)
Shield attenuation	2.1 dB (with 1 MHz)
	4 dB (at 4 MHz)
	6.3 dB (at 10 MHz)
	8 dB (at 16 MHz)
	9 dB (at 20 MHz)
	11.4 dB (at 31.25 MHz)
	16.5 dB (at 62.5 MHz)
	21.3 dB (at 100 MHz)
Flame resistance	according to UL 1685 (CSA FT 4)
Resistance to oil	Resistant to oil to a limited extent
Other resistance	UV resistant According to UL 1581, Section 1200
Ambient temperature (operation)	-40 °C ... 70 °C (cable, fixed installation)
	-40 °C ... 70 °C (Cable, flexible installation)
Ambient temperature (installation)	-20 °C ... 60 °C
Signal type/category	Ethernet, 100 Mbps
	PROFINET, 100 Mbps
	EtherCAT <sup>®</sup> , 100 Mbps

## Ambient conditions

Degree of protection	IP65
	IP67
Degree of protection	IP65/IP67
Ambient temperature (operation)	-25 °C ... 90 °C (M8 connectors)


## Standards and regulations

M8


Standards/specifications	IEC 61076-2-104
--------------------------	-----------------

Drawings

Circuit diagram



Schematic diagram



Pin assignment M8 plug, 4-pos., view male side


# Network cable - NBC-M 8MS/ 1,0-93B

1407344

<https://www.phoenixcontact.com/us/products/1407344>



Dimensional drawing



M8 x 1 male plug, straight version

# Network cable - NBC-M 8MS/ 1,0-93B



1407344

<https://www.phoenixcontact.com/us/products/1407344>

## Approvals



**EAC**

Approval ID: RU D-DE.HB35.B.00387

# Network cable - NBC-M 8MS/ 1,0-93B



1407344

<https://www.phoenixcontact.com/us/products/1407344>

## Classifications

### ECLASS

ECLASS-9.0	27060308
ECLASS-10.0.1	27060308
ECLASS-11.0	27060307

### ETIM

ETIM 8.0	EC001855
----------	----------

### UNSPSC

UNSPSC 21.0	26121600
-------------	----------

# Network cable - NBC-M 8MS/ 1,0-93B



1407344

<https://www.phoenixcontact.com/us/products/1407344>

## Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

# Network cable - NBC-M 8MS/ 1,0-93B



1407344

<https://www.phoenixcontact.com/us/products/1407344>

## Accessories

### Network cable

Network cable - NBC-M 8MS/.../... - 1408719

<https://www.phoenixcontact.com/us/products/1408719>



Network cable, Ethernet (100 Mbps), PROFINET (100 Mbps), EtherCAT® (100 Mbps), 4-position, Variable cable type, shielded, Plug straight M8 / IP67, coding: A, on free cable end, cable length: Free input (0.2 ... 40.0 m)

---

### Network cable

Network cable - NBC-M 8FS/.../... - 1408716

<https://www.phoenixcontact.com/us/products/1408716>



Network cable, Ethernet (100 Mbps), PROFINET (100 Mbps), EtherCAT® (100 Mbps), 4-position, Variable cable type, shielded, free cable end, on Socket straight M8 / IP67, coding: A, cable length: Free input (0.2 ... 40.0 m)

# Network cable - NBC-M 8MS/ 1,0-93B

1407344

<https://www.phoenixcontact.com/us/products/1407344>

## Torque screwdriver

Torque screwdriver - TSD 02 SAC - 1208487

<https://www.phoenixcontact.com/us/products/1208487>



Torque screwdriver, with preset torque of 0.2 Nm and 4 mm hexagonal drive for M8 connectors

---

## Tool

Tool - SAC BIT M8-D10 - 1208461

<https://www.phoenixcontact.com/us/products/1208461>



Nut for assembling M8 connectors with longitudinal knurl and a knurl diameter of 10 mm, for 4 mm hexagonal drive

# Network cable - NBC-M 8MS/ 1,0-93B

1407344

<https://www.phoenixcontact.com/us/products/1407344>

## Sealing cap

Sealing cap - PROT-M 8 FS-PA-CHAIN - 1430857

<https://www.phoenixcontact.com/us/products/1430857>

M8 sealing cap made of plastic with fixing band for sensor cables, for M8 plugs



---

## Cable-cutting tool

Cable-cutting tool - CUTFOX 12 - 1212128

<https://www.phoenixcontact.com/us/products/1212128>

**Cable cutter**, for copper and aluminum up to 12 mm diameter (up to 35 mm<sup>2</sup>)



# Network cable - NBC-M 8MS/ 1,0-93B



1407344

<https://www.phoenixcontact.com/us/products/1407344>

## Diagonal cutter

Diagonal cutter - CUTFOX-S VDE - 1212207

<https://www.phoenixcontact.com/us/products/1212207>



Diagonal cutter for hard (piano wire) and soft wires, VDE 1000 V AC/1500 V DC tested

---

## Stripping tool

Stripping tool - VS-CABLE-STRIP-VARIO - 1657407

<https://www.phoenixcontact.com/us/products/1657407>

Stripping tool, for the multi-level stripping of shielded cables



# Network cable - NBC-M 8MS/ 1,0-93B

1407344

<https://www.phoenixcontact.com/us/products/1407344>

## Diagonal cutter

Diagonal cutter - MICROFOX-SP-1 - 1212487

<https://www.phoenixcontact.com/us/products/1212487>



Electronic diagonal cutter, tapered head, without chamfer, with opening spring, non-reflective phosphate-treated surface, punched version

---

## Stripping tool

Stripping tool - WIREFOX 4 - 1212156

<https://www.phoenixcontact.com/us/products/1212156>



Stripping tool, for cables and conductors (especially for rubber and silicone insulations) from 0.1 - 4 mm<sup>2</sup>, self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 mm<sup>2</sup> stranded/1.5 mm<sup>2</sup> solid, replaceable stripping blade

# Network cable - NBC-M 8MS/ 1,0-93B

1407344

<https://www.phoenixcontact.com/us/products/1407344>

## Stripping tool

Stripping tool - WIREFOX-E 4 - 1212704

<https://www.phoenixcontact.com/us/products/1212704>



Stripping tool, for cables and conductors (especially for rubber and silicone insulations) from 0.1 - 4 mm<sup>2</sup>, self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 mm<sup>2</sup> stranded/1.5 mm<sup>2</sup> solid, replaceable stripping blade

---

## Stripping tool

Stripping tool - WIREFOX 10 - 1212150

<https://www.phoenixcontact.com/us/products/1212150>



Stripping tool, for cables and conductors from 0.02 - 10 mm<sup>2</sup>, self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 mm<sup>2</sup> stranded/1.5 mm<sup>2</sup> solid, replaceable stripping blade

# Network cable - NBC-M 8MS/ 1,0-93B



1407344

<https://www.phoenixcontact.com/us/products/1407344>

## Protective hose adapter

Protective hose adapter - WP-CTA POM 13,0 BK - 1422884

<https://www.phoenixcontact.com/us/products/1422884>



Protective hose adapter, for corrugated hoses with a nominal size of 13 (10 x 13), corrugated in parallel

---

## Protective hose

Protective hose - WP-PA HF 13,0 BK - 3240681

<https://www.phoenixcontact.com/us/products/3240681>



Protective hose, material: PA 6, filament: without, UV-resistant: yes, flexible, degree of protection: IP68, color: black, inflammability class in acc. with UL 94: V0, inner diameter: 10 mm, Total length: 50 m

# Network cable - NBC-M 8MS/ 1,0-93B

1407344

<https://www.phoenixcontact.com/us/products/1407344>

## Protective hose

Protective hose - WP-PA HF-HB 13,0 BK - 3240839

<https://www.phoenixcontact.com/us/products/3240839>



Protective hose, material: PA 6, filament: without, UV-resistant: yes, flexible, degree of protection: IP68, color: black, inflammability class in acc. with UL 94: HB, inner diameter: 10 mm, Total length: 50 m

---

## Data connector

Data connector - SACC-M12MSD-4QO SH PN - 1411068

<https://www.phoenixcontact.com/us/products/1411068>



Data connector, PROFINET CAT5 (100 Mbps), 4-position, halogen-free, shielded, Plug straight M12 SPEEDCON, Coding: D, Insulation displacement connection, knurl material: Zinc die-cast, nickel-plated, external cable diameter 5 mm ... 9.7 mm

# Network cable - NBC-M 8MS/ 1,0-93B



1407344

<https://www.phoenixcontact.com/us/products/1407344>

## Data connector

Data connector - SACC-M12MRD-4Q SH PN - 1554539

<https://www.phoenixcontact.com/us/products/1554539>



Data connector, PROFINET CAT5 (100 Mbps), 4-position, shielded, Plug angled M12, Coding: D, Insulation displacement connection, knurl material: Nickel-plated brass, external cable diameter 4 mm ... 8 mm

---

## Data connector

Data connector - SACC-M12FSD-4QO SH PN - 1411071

<https://www.phoenixcontact.com/us/products/1411071>



Data connector, PROFINET CAT5 (100 Mbps), 4-position, halogen-free, shielded, Socket straight M12 SPEEDCON, Coding: D, Insulation displacement connection, knurl material: Zinc die-cast, nickel-plated, external cable diameter 5 mm ... 9.7 mm

# Network cable - NBC-M 8MS/ 1,0-93B



1407344

<https://www.phoenixcontact.com/us/products/1407344>

## Data connector

Data connector - SACC-M12FRD-4Q SH PN - 1554542

<https://www.phoenixcontact.com/us/products/1554542>



Data connector, PROFINET CAT5 (100 Mbps), 4-position, shielded, Socket angled M12, Coding: D, Insulation displacement connection, knurl material: Nickel-plated brass, external cable diameter 4 mm ... 8 mm

---

## Conductor connectors

Conductor connectors - SACC-CC-4QO SH PN - 1414416

<https://www.phoenixcontact.com/us/products/1414416>



Cable connector, PROFINET CAT5 (100 Mbps), 4-pos., halogen-free, shielded, insulation displacement connection, housing material: zinc die-cast, nickel-plated, outer cable diameter of 5 mm ... 9.7 mm

# Network cable - NBC-M 8MS/ 1,0-93B

1407344

<https://www.phoenixcontact.com/us/products/1407344>

## Data connector

Data connector - SACC-M12MSD-4PL SH PN - 1424682

<https://www.phoenixcontact.com/us/products/1424682>



Data connector, PROFINET CAT5 (100 Mbps), 4-position, shielded, Plug straight M12, Coding: D, Push-lock spring connection, knurl material: Zinc die-cast, nickel-plated, external cable diameter 4 mm ... 8 mm

---

## Data connector

Data connector - SACC-M12MRD-4PL SH PN - 1424684

<https://www.phoenixcontact.com/us/products/1424684>



Data connector, PROFINET CAT5 (100 Mbps), 4-position, shielded, Plug angled M12, Coding: D, Push-lock spring connection, knurl material: Zinc die-cast, nickel-plated, external cable diameter 4 mm ... 8 mm

# Network cable - NBC-M 8MS/ 1,0-93B

1407344

<https://www.phoenixcontact.com/us/products/1407344>

## Data connector

Data connector - SACC-M12FSD-4PL SH PN - 1424683

<https://www.phoenixcontact.com/us/products/1424683>



Data connector, PROFINET CAT5 (100 Mbps), 4-position, shielded, Socket straight M12, Coding: D, Push-lock spring connection, knurl material: Zinc die-cast, nickel-plated, external cable diameter 4 mm ... 8 mm

---

## Data connector

Data connector - SACC-M12FRD-4PL SH PN - 1424685

<https://www.phoenixcontact.com/us/products/1424685>



Data connector, PROFINET CAT5 (100 Mbps), 4-position, shielded, Socket angled M12, Coding: D, Push-lock spring connection, knurl material: Zinc die-cast, nickel-plated, external cable diameter 4 mm ... 8 mm

# Network cable - NBC-M 8MS/ 1,0-93B

1407344

<https://www.phoenixcontact.com/us/products/1407344>

## Data connector

Data connector - SACC-M12MSD-4CT-CM SH PN - 1422846

<https://www.phoenixcontact.com/us/products/1422846>



Data connector, PROFINET CAT5 (100 Mbps), 4-position, shielded, Plug straight M12, Coding: D, Crimp connection, knurl material: Zinc die-cast, tin-plated, external cable diameter 4.5 mm ... 7.5 mm, without crimp contacts

---

## Data connector

Data connector - SACC-M12MRD-4CT-CM SH PN - 1422847

<https://www.phoenixcontact.com/us/products/1422847>



Data connector, PROFINET CAT5 (100 Mbps), 4-position, shielded, Plug angled M12, Coding: D, Crimp connection, knurl material: Zinc die-cast, tin-plated, external cable diameter 4.5 mm ... 7.5 mm, without crimp contacts

# Network cable - NBC-M 8MS/ 1,0-93B

1407344

<https://www.phoenixcontact.com/us/products/1407344>

## Data connector

Data connector - SACC-M12FSD-4CT-CM SH PN - 1422848

<https://www.phoenixcontact.com/us/products/1422848>



Data connector, PROFINET CAT5 (100 Mbps), 4-position, shielded, Socket straight M12, Coding: D, Crimp connection, knurl material: Zinc die-cast, tin-plated, external cable diameter 4.5 mm ... 7.5 mm, without crimp contacts

---

## Data connector

Data connector - SACC-M12FRD-4CT-CM SH PN - 1422849

<https://www.phoenixcontact.com/us/products/1422849>



Data connector, PROFINET CAT5 (100 Mbps), 4-position, shielded, Socket angled M12, Coding: D, Crimp connection, knurl material: Zinc die-cast, tin-plated, external cable diameter 4.5 mm ... 7.5 mm, without crimp contacts

# Network cable - NBC-M 8MS/ 1,0-93B

1407344

<https://www.phoenixcontact.com/us/products/1407344>

## RJ45 connector

RJ45 connector - VS-PN-RJ45-5-Q/IP20 - 1658435

<https://www.phoenixcontact.com/us/products/1658435>



RJ45 connector, type: RJ45, degree of protection: IP20, number of positions: 4, 100 Mbps, CAT5 (IEC 11801:2002), material: PA, connection method: IDC fast connection, cable outlet: straight, color: traffic grey A RAL 7042, PROFINET

---

## RJ45 connector

RJ45 connector - CUC-IND-C1ZNI-S/R4IP8 - 1421126

<https://www.phoenixcontact.com/us/products/1421126>



RJ45 connector, type: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5 (IEC 11801:2002), material: Zinc die-cast, connection method: IDC fast connection, connection cross section: AWG 23- 22, cable outlet: straight, color: green, PROFINET

# Network cable - NBC-M 8MS/ 1,0-93B

1407344

<https://www.phoenixcontact.com/us/products/1407344>

## RJ45 connector

RJ45 connector - CUC-IND-C1ZNI-T/R4IP8 - 1421128

<https://www.phoenixcontact.com/us/products/1421128>



RJ45 connector, type: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5 (IEC 11801:2002), material: Zinc die-cast, connection method: IDC fast connection, connection cross section: AWG 23- 22, cable outlet: angled, Ethernet/PROFINET

---

## RJ45 connector

RJ45 connector - CUC-IND-C1ZNI-B/R4IP8 - 1421127

<https://www.phoenixcontact.com/us/products/1421127>



RJ45 connector, type: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5 (IEC 11801:2002), material: Zinc die-cast, connection method: IDC fast connection, connection cross section: AWG 23- 22, cable outlet: angled, Ethernet/PROFINET

# Network cable - NBC-M 8MS/ 1,0-93B

1407344

<https://www.phoenixcontact.com/us/products/1407344>

## RJ45 connector

RJ45 connector - CUC-V14-C1ZNI-S/R4P8 - 1422664

<https://www.phoenixcontact.com/us/products/1422664>



Push-pull connector (version 14), die-cast zinc, with RJ45 connector insert, 8-pos., with IDC fast connection technology, for 1 and 7-wire cores, 23 ... 22 AWG, for cable diameter of 5.5 mm ... 10 mm

---

## RJ45 connector

RJ45 connector - CUC-V14-C1ZNI-T/R4P8 - 1422667

<https://www.phoenixcontact.com/us/products/1422667>



Push-pull connector (version 14), die-cast zinc, with RJ45 connector insert, 8-pos., with IDC fast connection technology, for 1 and 7-wire cores, 23 ... 22 AWG, for cable diameter of 5.5 mm ... 10 mm

# Network cable - NBC-M 8MS/ 1,0-93B



1407344

<https://www.phoenixcontact.com/us/products/1407344>

## RJ45 connector

RJ45 connector - CUC-V14-C1ZNI-B/R4P8 - 1422665

<https://www.phoenixcontact.com/us/products/1422665>



Push-pull connector (version 14), die-cast zinc, with RJ45 connector insert, 8-pos., with IDC fast connection technology, for 1 and 7-wire cores, 23 ... 22 AWG, for cable diameter of 5.5 mm ... 10 mm

---

Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)