

## Housing - HC-STA-D07-CHWS-1TTM25-EL-AL - 1419239

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Coupling housings D7, With single locking latch, Material: Die-cast aluminum, salt water resistant, Cable outlets: 1, straight, Height: 60.5 mm, Cable gland: none, Gland: Yes, 1x M25, Standard

As illustrated, but with M25 thread



### Key Commercial Data

Packing unit	1 STK
GTIN	 4 055626 159720
GTIN	4055626159720
Custom tariff number	85389099
Country of origin	China

### Technical data

#### Dimensions

Height	60.5 mm
Width	26.5 mm
Length	26.5 mm

#### Ambient conditions

Degree of protection of housing (IP)	IP66
	IP67
Degree of protection of housing (NEMA)	4 (UL 50e)
	4X (UL 50e)
	12 (UL 50e)
Ambient temperature (operation)	-40 °C ... 125 °C

#### General

# Housing - HC-STA-D07-CHWS-1TTM25-EL-AL - 1419239


## Technical data

### General

Note	for contact inserts HC-A03, A04, D07, D08, Q02, Q03, Q04, Q05, Q07, Q12
Size	D7
Housing type	Coupling housings
Locking type	With single locking latch
No. of cable outlets	1
Cable exit	straight
Screw connection	none
Type of the screw connection	1x M25
Housing material	Die-cast aluminum, salt water resistant
Housing surface material	Uncoated

## Drawings

Dimensional drawing



## Approvals

### Approvals

Approvals

EAC

Ex Approvals

### Approval details

EAC		EAC-Zulassung
-----	--	---------------

