

**Industrial Ethernet
IE-C6KS8VG0015XCSXXX-E**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Assembled IE cables, PROFINET, Cat 6_A, PVC, green,
M12 X-type

General ordering data

Type	IE-C6KS8VG0015XCSXXX-E
Order No.	1449470015
Version	Connecting cables, M12 X-type IP 67 straight male, Open, Cat.6 _A / Class E _A (ISO/IEC 11801 2010), PVC, 1.5 m
GTIN (EAN)	4050118263879
Qty.	1 pc(s).

**Industrial Ethernet
IE-C6KS8VG0015XCSXXX-E**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data
Dimensions and weights

Length	1.5 m	Length (inches)	0.059 inch
Net weight	0.001 g	Insulation cross-section	1.58 mm

Temperatures

Operating temperature, max.	80 °C	Operating temperature, min.	-40 °C
Storage temperature, max.	80 °C	Storage temperature, min.	-40 °C
Operating temperature	-40 °C...80 °C	Storage temperature	-40 °C...80 °C
Installation temperature	-40 °C...80 °C		

Standards

Standard, assembly	UL-Style 2461
--------------------	---------------

Cable structure

Cross-section	4*2*AWG 23/7	Insulation cross-section	1.58 mm
Colour sequence or wires - wire pairs	white/blue - blue, white/ orange - orange, white/ green - green, white/ brown - brown	Shielding	
Material sheath	PVC	Sheath diameter, max.	8.8 mm
Sheathing colour	green (RAL 6018)		S/FTP

Electrical properties of cable

Category	Cat.6 _A / Class E _A (ISO/IEC 11801 2010)	Test voltage: wire-wire-shield	800 V _{rms} , 50 Hz, 1 min
Speed	10 GBit/s		

Mechanical and material properties of cable

Min. bending radius, once only	4 *diameter	Min. bending radius, repetitive	8 *diameter
Pulling force	≤ 150 N	Speed	10 GBit/s
Resistance to spread of flame	in accordance with IEC 60332-1-2		

plug

Connector left	M12 X-type IP 67 straight male	Connector right	Open
----------------	--------------------------------	-----------------	------

Classifications

ETIM 6.0	EC002599	eClass 6.2	27-06-03-90
eClass 9.1	27-06-03-08		

Approvals

ROHS	Conform
------	---------

Data sheet**Industrial Ethernet
IE-C6KS8VG0015XCSXXX-E**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

White, Orange	1	M12
Orange	2	
White, Green	3	
Green	4	
White, Brown	5	
Brown	6	
White, Blue	7	
Blue	8	
