

**Industrial Ethernet
IE-C6EL8UG0050XCSXCS-E**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Assembled IE cables for EtherNet/IP applications

- with bayonet connector according to IEC 61076-3-106 var. 1, cat. 5, sheathed
- with plug-in connector, type M12 X, cat. 6A, according to IEC 61076-2-109 and RJ45 plug-in connector for 10 GBit/s applications

General ordering data

Type	IE-C6EL8UG0050XCSXCS-E
Order No.	1463640050
Version	System cable, M12 X-type IP 67 straight male, M12 X-type IP 67 straight male, Cat.6 _A / Class E _A (ISO/IEC 11801 2010), PUR, 5 m
GTIN (EAN)	4050118270846
Qty.	1 pc(s).

Industrial Ethernet
IE-C6EL8UG0050XCSXCS-E

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Dimensions and weights

Length	5 m	Length (inches)	0.197 inch
Net weight	250 g	Insulation cross-section	0.98 mm

Temperatures

Operating temperature, max.	80 °C	Operating temperature, min.	-40 °C
Storage temperature, max.	80 °C	Storage temperature, min.	-40 °C
Operating temperature	-40 °C...80 °C	Storage temperature	-40 °C...80 °C
Installation temperature	-20 °C...60 °C		

Standards

Impervious to smoke	gemäß IEC 61034	Standard, assembly	UL Style 20963
---------------------	-----------------	--------------------	----------------

Cable structure

Copper diameter	0.48 µm	Wiring	EIA/TIA T568 B
Wire material	Stranded tin-plated copper wire	Standard designations	S/FTP, LIO2YSC11Y 4x2x0.15 PIMF FRNC GN
Strands	7	Cross-section	4*2*AWG 26/7 - 4*2*0.128 mm ²
Insulation	PE	Insulation cross-section	0.98 mm
No. of wires	8	Arrangement of wire cores	Twisted pair
Wire pair shielding		Colour sequence or wires - wire pairs	white - blue, white - orange, white - green, white - brown
Shielding	Aluminium foil	Complete shielding	Shielding braid made from copper wiring
Shielding braid thickness	S/FTP	Material sheath	PUR
Sheath diameter, min.	0.1 mm	Sheath diameter, max.	6.7 mm
Sheathing colour	6.1 mm		
	green (RAL 6018)		

Electrical properties of cable

Category	Cat.6 _A / Class E _A (ISO/IEC 11801 2010)	Test voltage: wire-wire-shield	700 V _{rms} , 50 Hz, 1 min
Characteristic impedance	100 ± 5 Ω at 100MHz	Loop resistance	290 Ω/km
Transfer impedance	15 mΩ/m at 1 MHz, 10 mΩ/m at 10 MHz, 30 mΩ/m at 30 MHz	Signal propagation time	5.2 ns/m
Speed	10 GBit/s		

Mechanical and material properties of cable

Min. bending radius, once only	5 *diameter	Min. bending radius, repetitive	10 *diameter
Speed	10 GBit/s	Abrasion resistance	very good
Resistance to spread of flame	in accordance with IEC 60332-1-2	Resistance to oils	in accordance with IEC 60811-2-1
Halogen	halogen-free, according to IEC 60754-1	Impervious to smoke	gemäß IEC 61034

plug

Connector left	M12 X-type IP 67 straight male	Connector right	M12 X-type IP 67 straight male
----------------	--------------------------------	-----------------	--------------------------------

Creation date April 13, 2018 12:04:24 PM CEST

Data sheet**Industrial Ethernet
IE-C6EL8UG0050XCSXCS-E**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data**Classifications**

ETIM 5.0	EC000748	ETIM 6.0	EC002599
eClass 6.2	27-06-03-90	eClass 7.1	27-06-03-90
eClass 8.1	27-06-03-90	eClass 9.0	27-06-03-90
eClass 9.1	27-06-03-08		

Approvals

ROHS	Conform
------	---------

Data sheet

**Industrial Ethernet
IE-C6EL8UG0050XCSXCS-E**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Drawings

Wiring

M12	1	White, Orange	1	M12
	2	Orange	2	
	3	White, Green	3	
	4	Green	4	
	5	White, Brown	5	
	6	Brown	6	
	7	White, Blue	7	
	8	Blue	8	

Pinning

