

Specification Sheet

Part Number: 150-55948



2-Piece Cable Tie/Fir Tree Mount, 6.0"L, 0.17" - 0.20" Mounting Hole Diameter, PA46, Gray, 500/pkg

Article Number 150-55948

Type T30RFT5

Color Natural (NA) Gray (GY)

Features & Benefits

- Friction tab inside the fir tree allows the tie to sit in mount without falling out prior to installation.
- Fir tree provides low insertion effort yet demonstrates high extraction resistance.
- Disc feature prevents rattling in high-vibration applications and protects against debris ingress.

Quantity Per bag

| | |
|--|---|
| Product Description | HellermannTyton's fir tree mounts provide a secure grip in a mounting hole. The mount can slide along the cable tie to adjust orientation as needed. Fir tree mounts are designed to provide a low insertion force and high extraction force. This mount is sold as an assembly with the cable tie. |
| Short Description | 2-Piece Cable Tie/Fir Tree Mount, 6.0"L, 0.17" - 0.20" Mounting Hole Diameter, PA46, Gray, 500/pkg |
| Global Part Name | T30RFT5-PA46-NA/GY |
| Minimum Tensile Strength (Imperial) | 30.0 |
| Minimum Tensile Strength (Metric) | 135 |
| Length L (Imperial) | 6.0 |
| Length L (Metric) | 150.0 |
| Fixation Method | Fir Tree |
| Identification Plate Position | none |
| Tie Closure | plastic pawl |
| Variant | Inside Serrated |
| Width W (Imperial) | 0.14 |
| Width W (Metric) | 3.5 |
| Bundle Diameter Min (Imperial) | 0.06 |

| | |
|--|--------------|
| Bundle Diameter Min (Metric) | 3.5 |
| Bundle Diameter Max (Imperial) | 1.4 |
| Bundle Diameter Max (Metric) | 34.0 |
| Thickness T (Imperial) | 0.043 |
| Thickness T (Metric) | 1.1 |
| Height H (Imperial) | 0.04 |
| Height H (Metric) | 1.2 |
| Panel Thickness Min(Imperial) | 0.03 |
| Panel Thickness Max(Imperial) | 0.12 |
| Panel Thickness Min (Metric) | 0.7 |
| Panel Thickness Max (Metric) | 3.0 |
| Mounting Hole Diameter D (Imperial) | 0.17 - 0.2 |
| Mounting Hole Diameter D (Metric) | 4.5 - 5.0 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.177 |
| Mounting Hole Diameter D Max (Imperial) | 0.197 |
| Mounting Hole Diameter D Max (Metric) | 5.0 |
| Disc Diameter(Metric) | 16.0 |

| | |
|---------------------------------------|-----------------------------------|
| Disc Diameter (Imperial) | 0.63 |
| Material | Polyamide 4.6 (PA46) |
| Material Shortcut | PA46 |
| Material Cable Tie | Polyamide 4.6 (PA46) |
| Flammability | UL 94 V2 |
| Operating Temperature (Metric) | -40°F to +302°F (-40°C to +150°C) |
| Reach Complaint(Article 33) | Yes |
| ROHS Complaint | Yes |
| Package Quantity(Imperial) | 500 |
| Package Quantity (Metric) | 500 |
| Customs Number | 3926909988 |
| Content Unit(BMEcat) | pcs. |
| Weight (Metric) | 1.2 |

