

## 1533P Multi-Conductor - Category 5e Nonbonded-Pair Cable



For more Information  
please call

1-800-Belden1

**Description:**

24 AWG solid bare copper conductors, plenum, FEP Teflon® insulation, twisted pairs, overall Beldfoil® shield, drain wire, RJ-45 compatible, see color code chart (below), Flamarrest® jacket (red, orange, yellow, green, blue, gray or natural).

**Usage (Overall)****Suitable Applications:**

Premise Horizontal Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG  
 ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video,  
 AES/EBU, Digital Video, RS-422, Noisy Environments, 100MHz Category 5e

**Physical Characteristics (Overall)****Conductor****AWG:**

| # Pairs | AWG | Stranding | Conductor Material |
|---------|-----|-----------|--------------------|
| 4       | 24  | Solid     | BC - Bare Copper   |

**Insulation****Insulation Material:**

| Insulation Material                  |
|--------------------------------------|
| FEP - Fluorinated Ethylene Propylene |

**Outer Shield****Outer Shield Material:**

| Outer Shield Trade Name | Type | Outer Shield Material        | Coverage (%) |
|-------------------------|------|------------------------------|--------------|
| Beldfoil®               | Tape | Aluminum Foil-Polyester Tape | 100          |

**Outer Shield Drain Wire AWG:**

| AWG | Stranding | Drain Wire         | Conductor Material |
|-----|-----------|--------------------|--------------------|
| 24  | 7x32      | TC - Tinned Copper |                    |

**Outer Jacket****Outer Jacket Material:**

| Outer Jacket Trade Name | Outer Jacket Material                 |
|-------------------------|---------------------------------------|
| Flamarrest®             | LS PVC - Low Smoke Polyvinyl Chloride |

**Overall Cabling**

**Overall Nominal Diameter:** 0.235 in.

**Pair****Pair Color Code Chart:**

| Number | Color                        |
|--------|------------------------------|
| 1      | White/Blue Stripe & Blue     |
| 2      | White/Orange Stripe & Orange |
| 3      | White/Green Stripe & Green   |
| 4      | White/Brown Stripe & Brown   |

**Mechanical Characteristics (Overall)**

**Operating Temperature Range:** 0°C To +75°C

**Bulk Cable Weight:** 34 lbs/1000 ft.

**Max. Recommended Pulling Tension:** 25 lbs.

## 1533P Multi-Conductor - Category 5e Nonbonded-Pair Cable

|                                        |       |
|----------------------------------------|-------|
| Min. Bend Radius (Install)/Minor Axis: | 1 in. |
|----------------------------------------|-------|

## Applicable Specifications and Agency Compliance (Overall)

## Applicable Standards &amp; Environmental Programs

|                                       |                                                      |
|---------------------------------------|------------------------------------------------------|
| NEC/(UL) Specification:               | CMP, UL444                                           |
| CEC/C(UL) Specification:              | CMP                                                  |
| Other Standards:                      | 11801 Category 5                                     |
| EU CE Mark:                           | Yes                                                  |
| EU Directive 2000/53/EC (ELV):        | Yes                                                  |
| EU Directive 2002/95/EC (RoHS):       | Yes                                                  |
| EU RoHS Compliance Date (mm/dd/yyyy): | 01/01/2005                                           |
| EU Directive 2002/96/EC (WEEE):       | Yes                                                  |
| EU Directive 2003/11/EC (BFR):        | Yes                                                  |
| CA Prop 65 (CJ for Wire & Cable):     | Yes                                                  |
| MII Order #39 (China RoHS):           | Yes                                                  |
| Telecommunications Standards:         | 568-B.2 Category 5e                                  |
| Other Specification:                  | NEMA WC-63.1 Category 5e, UL Verified to Category 5e |

## Flame Test

|                 |          |
|-----------------|----------|
| UL Flame Test:  | NFPA 262 |
| CSA Flame Test: | FT6      |

## Plenum/Non-Plenum

|                    |       |
|--------------------|-------|
| Plenum (Y/N):      | Yes   |
| Non-Plenum Number: | 1533R |

## Electrical Characteristics (Overall)

## Nom. Mutual Capacitance:

|                     |
|---------------------|
| Capacitance (pF/ft) |
| 15                  |

|                                           |     |
|-------------------------------------------|-----|
| Maximum Capacitance Unbalance (pF/100 m): | 330 |
|-------------------------------------------|-----|

## Nominal Velocity of Propagation:

|        |
|--------|
| VP (%) |
| 70     |

## Maximum Delay:

|                  |
|------------------|
| Delay (ns/100 m) |
| 538 @ 100MHz     |

## Max. Delay Skew:

|                       |
|-----------------------|
| Delay Skew (ns/100 m) |
| 45                    |

## Maximum Conductor DC Resistance:

|                        |
|------------------------|
| DCR @ 20°C (Ohm/100 m) |
| 9.38                   |

## Max. Operating Voltage - UL:

|           |
|-----------|
| Voltage   |
| 300 V RMS |

## Maximum DCR Unbalanced:

|                          |
|--------------------------|
| DCR Unbalance @ 20°C (%) |
| 3                        |

## 1533P Multi-Conductor - Category 5e Nonbonded-Pair Cable

## Electrical Characteristics-Premise (Overall)

Premise Cable Electrical Table 1:

| Freq. (MHz) | Max. Attenuation (dB/100 m) | Min. NEXT (dB) | Min. PSNEXT (dB) | Min. ACR (dB) | Min. PSACR (dB) | Min RL (dB) | Min. SRL (dB) |
|-------------|-----------------------------|----------------|------------------|---------------|-----------------|-------------|---------------|
| 1           | 2.0                         | 65.3           | 62.3             | 60.3          | 60.3            | 20.0        | 23.0          |
| 4           | 4.1                         | 56.3           | 53.3             | 49.2          | 49.2            | 23.0        | 23.0          |
| 8           | 5.8                         | 51.8           | 48.8             | 43.0          | 43.0            | 24.5        | 24.5          |
| 10          | 6.5                         | 50.3           | 47.3             | 40.8          | 40.8            | 25.0        | 25.0          |
| 16          | 8.2                         | 47.3           | 44.3             | 36.0          | 36.0            | 25.0        | 25.0          |
| 20          | 9.3                         | 45.8           | 42.8             | 33.5          | 33.5            | 25.0        | 25.0          |
| 25          | 10.4                        | 44.3           | 41.3             | 30.9          | 30.9            | 24.3        | 24.3          |
| 31.25       | 11.7                        | 42.9           | 39.9             | 28.2          | 28.2            | 23.6        | 23.6          |
| 62.5        | 17.0                        | 38.4           | 35.4             | 18.4          | 18.4            | 21.5        | 21.5          |
| 100         | 22.0                        | 35.3           | 32.3             | 10.3          | 10.3            | 20.1        | 20.1          |

Premise Cable Electrical Table 2:

| Freq. (MHz) | Input (Unfitted) Imp. (Ohms) | Fitted Impedance | Min. ELFEXT (dB) | Min. PSELFEXT (dB) |
|-------------|------------------------------|------------------|------------------|--------------------|
| 1           | 100 ± 15                     | 100 ± 15         | 63.8             | 60.8               |
| 4           | 100 ± 15                     | 100 ± 15         | 51.7             | 48.7               |
| 8           | 100 ± 15                     | 100 ± 15         | 45.7             | 42.7               |
| 10          | 100 ± 15                     | 100 ± 15         | 43.8             | 40.8               |
| 16          | 100 ± 15                     | 100 ± 15         | 39.7             | 36.7               |
| 20          | 100 ± 15                     | 100 ± 15         | 37.7             | 34.7               |
| 25          | 100 ± 15                     | 100 ± 15         | 35.8             | 32.8               |
| 31.25       | 100 ± 15                     | 100 ± 15         | 33.9             | 30.9               |
| 62.5        | 100 ± 15                     | 100 ± 15         | 27.8             | 24.8               |
| 100         | 100 ± 15                     | 100 ± 15         | 23.8             | 20.8               |

## Notes (Overall)

**Notes:** Shield is bonded to jacket inner wall for electrical stability. RJ-45 Compatible. Jacket sequentially marked at 2 ft. intervals.  
Third party verified to TIA/EIA-568-B.2, Category 5e.

## Related Documents:

No related documents are available for this product

## Put Ups and Colors:

| Item #         | Putup    | Ship Weight | Color       | Notes | Item Desc                |
|----------------|----------|-------------|-------------|-------|--------------------------|
| 1533P D15A1000 | 1,000 FT | 37.000 LB   | BLUE        |       | CAT5E 4PR F/UTP CMP RIB  |
| 1533P D15I1000 | 1,000 FT | 35.000 LB   | BLUE        | C     | CAT5E 4PR F/UTP CMP REEL |
| 1533P 002A1000 | 1,000 FT | 37.000 LB   | RED         |       | CAT5E 4PR F/UTP CMP RIB  |
| 1533P 002I1000 | 1,000 FT | 35.000 LB   | RED         | C     | CAT5E 4PR F/UTP CMP REEL |
| 1533P 003A1000 | 1,000 FT | 37.000 LB   | ORANGE      |       | CAT5E 4PR F/UTP CMP RIB  |
| 1533P 003I1000 | 1,000 FT | 35.000 LB   | ORANGE      | C     | CAT5E 4PR F/UTP CMP REEL |
| 1533P 004A1000 | 1,000 FT | 37.000 LB   | YELLOW      |       | CAT5E 4PR F/UTP CMP RIB  |
| 1533P 004I1000 | 1,000 FT | 35.000 LB   | YELLOW      | C     | CAT5E 4PR F/UTP CMP REEL |
| 1533P 005A1000 | 1,000 FT | 37.000 LB   | GREEN, DARK |       | CAT5E 4PR F/UTP CMP RIB  |
| 1533P 005I1000 | 1,000 FT | 35.000 LB   | GREEN, DARK | C     | CAT5E 4PR F/UTP CMP REEL |
| 1533P 008A1000 | 1,000 FT | 37.000 LB   | GRAY        |       | CAT5E 4PR F/UTP CMP RIB  |
| 1533P 008I1000 | 1,000 FT | 35.000 LB   | GRAY        | C     | CAT5E 4PR F/UTP CMP REEL |
| 1533P 010A1000 | 1,000 FT | 37.000 LB   | BLACK       |       | CAT5E 4PR F/UTP CMP RIB  |
| 1533P 010I1000 | 1,000 FT | 35.000 LB   | BLACK       | C     | CAT5E 4PR F/UTP CMP REEL |
| 1533P 877A1000 | 1,000 FT | 37.000 LB   | NATURAL     |       | CAT5E 4PR F/UTP CMP RIB  |
| 1533P 877I1000 | 1,000 FT | 35.000 LB   | NATURAL     | C     | CAT5E 4PR F/UTP CMP REEL |

**Notes:**

C = CRATE REEL PUT-UP.

## 1533P Multi-Conductor - Category 5e Nonbonded-Pair Cable

Revision Number: 1    Revision Date: 04-23-2009

© 2011 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.