

[PRODUCTS](#)

## Rocker switches

[Pushbutton switches](#)[Toggle switches](#)[Slide switches](#)[Rotary switches](#)[Foot switches](#)[Tact and key switches](#)[Snap-action switches](#)[Micro-signal switches](#)[ECO switches](#)[Sensors](#)[Push'n'Drive](#)[Systems and modules](#)[Accessories](#)[General information](#)[Catalog request / download](#)
[PRODUCTS](#) ▶ [ROCKER SWITCHES](#)

## SERIES 1550 - SINGLE-POLE ROCKER SWITCHES - TO 16 (4) A 250 V AC


[◀ Show previous product](#)
[Show next product ▶](#)

1552.3117

[Drawing](#)


Similar to original product

[→ Print data sheet](#)

Product number	1552.3117
Actuator color / printing	
Inrush current (capacitive)	100 A
Switching function	ON / OFF switch (DPST)
Number of poles	2-pole
connections	Quick-connect terminal, 6.3
Mechanical life endurance	5E4
Rating IEC	10 (4) A 250 V AC 5E4 16 (4) A 250 V AC 1E4
Rating North America	20 A 125 V AC 1 HP 20 A 250 V AC 2 HP 16 A 125 V AC 1 HP 16 A 250 V AC 2 HP
Contact resistance (new condition)	< 100 (1 A 12 V DC) mOhm
Insulation resistance (new condition)	> 100 (500 V DC) MOhm
Proof tracking	250 PTI
Protection type	Connection IP40
Ambient temperature	-20 °C... +100 °C
Ambient temperature	-20 °C... +55 °C
Flammability	UL 94 V-0
Glow wire test temperature	850 °C
Actuators and additional actuators	FA, black
Housing description	FA, black
Contact material	Ag
Contact distance	≥ 3 mm
Plug force of the terminals	≤ 80 N
Approval marks	cCSAus / CSA / UL / BNEC 05
Suitable for appliances of protection class	II
EN 60335 cap. 30 conform "G"	yes