

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [1552410026](#)
Status: **Active**
Overview: Flamar Standard and Custom Cables for Industrial Automation
Description: Flamar Sensor Cable, TPE Jacket, Braided Shielding Overall, 5 Circuits, 0.34mm² / 22 AWG, 6.40mm (.252") Diameter, 500.0m (1640.42') Length, Black

Documents:

[Product Specification 1552400001-P1E \(PDF\)](#)
[Brochure \(PDF\)](#)

[RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification

CSA LL107556
 UL E470965

General

Product Family Cable
 Series [155241](#)
 Crimp Quality Equipment Yes
 Geographic Area Global
 Overview [Flamar Standard and Custom Cables for Industrial Automation](#)
 Product Name Flamar, Signal and Control
 UPC 889056458924

Physical

Bending Radius - Minimum > 10xOD
 Cable Length 500.0m
 Circuits (Loaded) 5
 Color - Cable Jacket Black
 Insulation PVC
 Material - Outer Jacket TPE
 Net Weight 0.062/kg
 Outer Jacket Diameter 6.40mm
 Packaging Type Reel
 Temperature Range - Operating -40° to +105°C
 Wire Size AWG 22
 Wire Size mm² 0.34
 Wire/Cable Type UL Listed PLTC

Electrical


Current - Maximum per Contact Contact Molex
 Voltage - Maximum 300V

Material Info

Engineering Number 1X500M

Reference - Drawing Numbers

Product Specification 1552400001-P1E



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Compliant
REACH SVHC
 Not Reviewed
Halogen-Free
Status
Not Reviewed

China RoHS

China ROHS Green Image
 ELV Not Relevant
 RoHS Phthalates Not Contained

For more information, please visit [Contact US](#)

Search Parts in this Series

[155241 Series](#)

Use With

Nano-Change (M8) [120091](#) , Micro-Change (M12) [120071](#) , Ultra-Lock (M12) [120085](#)