

157-00119

Article Number: 157-00119



Description: Offset Fir Tree Cable Tie, 9.0" Long, 50lb, Mounting Diameter .24" - .28", PA66HIRHS, Gray, 500/pkg

Base Data	Local Order Number	157-00119
	Type	T50ROSFT6SO25A
	Color	Gray (GY)
	Features and Benefits	<ul style="list-style-type: none"> <li>• One-piece cable tie and fixing offers a simple and easy to use method of bundling and fixing cables, through the design of the fir tree by ensuring positive and secure fixing into panels with thicknesses from 0.6-6.65mm.</li> <li>• The offset on the cable tie creates an alternate solution when an offset fixing option is required and a tape clip cannot be used due to the design which reduces the potential of the bundle flexing or shifting.</li> <li>• The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.</li> </ul>
	Quantity Per	bag
	Product Description	<p>HellermannTyton's Off-Set Fir Tree Cable Tie and fixing offers a simple and easy to use method of bundling and fixing cables, the design of the fir tree ensures a positive and secure fixing into panels with thicknesses from .2" - .26" or threaded blind holes.</p> <p>The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.</p>
	Short Description	Offset Fir Tree Cable Tie, 9.0" Long, 50lb, Mounting Diameter .24" - .28", PA66HIRHS, Gray, 500/pkg
Product Dimensions	Minimum Tensile Strength (Imperial)	50.0lbs
	Minimum Tensile Strength (Metric)	222.0N
	Length L (Imperial)	9.1"
	Length L (Metric)	230.0mm
	Identification Plate Position	none
	Length L2 (Metric)	25.0mm
	Releasable Closure	No
	Width W (Metric)	5.1mm
	Height H (Imperial)	0.9"
	Height H (Metric)	21.2mm
	Bundle Diameter Min. (Imperial)	0.06"

157-00119



Product Dimensions	Bundle Diameter Min. (Metric)	1.6mm
	Bundle Diameter Max. (Imperial)	1.97"
	Bundle Diameter Max. (Metric)	50.0mm
	Disc Diameter (Metric)	19.0mm
	Panel Thickness Max. (Imperial)	0.26"
	Panel Thickness Max. (Metric)	6.65mm
	Panel Thickness Min. (Imperial)	0.02"
	Panel Thickness Min. (Metric)	0.6mm
	Mounting Hole Diameter D (Imperial)	0.2-0.27"
	Mounting Hole Diameter D (Metric)	6.1 - 7.0 mm
	Mounting Hole Diameter D Max. (Metric)	7.0mm
	Mounting Hole Diameter D Min. (Metric)	6.1mm
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
	Material Shortcut	PA66HIRHS
	Flammability	UL94 V2
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Metric)	500
	Customs Number(Schedule B)	3926909987