

Crimp contact - CK4,0-ED-10,00ST AG - 1586198

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Turned 4.0 crimp contact, single male contact, 10 mm² conductor cross section, silver-plated



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	25 pc
Weight per Piece (excluding packing)	3.2 g
Custom tariff number	85369010
Country of origin	Germany

Technical data

Electrical characteristics

Note	for HC-M-02 modules
------	---------------------

Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C
---------------------------------	-------------------

Mechanical characteristics

Conductor cross section	10 mm ²
Connection cross section AWG	8
Stripping length of the individual wire	18 mm (For wire $\varnothing \geq 6.4$ mm) 15 mm (For wire $\varnothing \geq 4.3$ mm)
Insertion/withdrawal cycles	≥ 500

General

Type	Individual male contact
Series	HC-M-03
Connection method	Crimp connection

Crimp contact - CK4,0-ED-10,00ST AG - 1586198

Technical data

Material data

Contact material	Copper alloy
Contact surface material	silver-plated

Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209
eCl@ss 8.0	27440204
eCl@ss 9.0	27440204

ETIM

ETIM 3.0	EC001032
ETIM 4.0	EC001134
ETIM 5.0	EC000796

UNSPSC

UNSPSC 6.01	30211923
UNSPSC 7.0901	39121522
UNSPSC 11	39121522
UNSPSC 12.01	39121522
UNSPSC 13.2	39121522

Approvals

Approvals

Approvals

EAC

Ex Approvals

Crimp contact - CK4,0-ED-10,00ST AG - 1586198

Approvals

Approvals submitted

Approval details

EAC

Drawings

Dimensional drawing

