


SKT 130



Stud Thyristor

Line Thyristor

SKT 130

Features


- Hermetic metal case with glass insulator
- Threaded stud ISO M16x1,5
- International standard case

Typical Applications*

- DC motor control
(e. g. for machine tools)
- Controlled rectifiers
(e. g. for battery charging)
- AC controllers
(e. g. for temperature control)
- Recommended snubber network
e. g. for $V_{VRMS} \leq 400 \text{ V}$:
 $R = 33 \Omega / 13 \text{ W}$, $C = 0,47 \mu\text{F}$

V_{RSM} V	V_{RRM}, V_{DRM} V	$I_{TRMS} = 220 \text{ A}$ (maximum value for continuous operation) $I_{TAV} = 130 \text{ A}$ (sin. 180; $T_c = 85^\circ\text{C}$)		
500	400	SKT 130/04D		
700	600	SKT 130/06D		
900	800	SKT 130/08D		
1300	1200	SKT 130/12E		
1500	1400	SKT 130/14E		
1700	1600	SKT 130/16E		

Symbol	Conditions	Values	Units
I_{TAV}	sin. 180; $T_c = 100 (85)^\circ\text{C}$;	97 (130)	A
I_D	K1,1; $T_a = 45^\circ\text{C}$; B2 / B6	90 / 125	A
	K0,55; $T_a = 45^\circ\text{C}$; B2 / B6	140 / 200	A
I_{RMS}	K0,55; $T_a = 45^\circ\text{C}$; W1C	155	A
I_{TSM}	$T_{vj} = 25^\circ\text{C}$; 10 ms	3500	A
	$T_{vj} = 130^\circ\text{C}$; 10 ms	3000	A
i^2t	$T_{vj} = 25^\circ\text{C}$; 8,35 ... 10 ms	61000	A ² s
	$T_{vj} = 130^\circ\text{C}$; 8,35 ... 10 ms	45000	A ² s
V_T	$T_{vj} = 25^\circ\text{C}$; $I_T = 500 \text{ A}$	max. 2,25	V
$V_{T(TO)}$	$T_{vj} = 130^\circ\text{C}$	max. 1,2	V
r_T	$T_{vj} = 130^\circ\text{C}$	max. 2,2	m Ω
I_{DD}, I_{RD}	$T_{vj} = 130^\circ\text{C}$; $V_{RD} = V_{RRM}$; $V_{DD} = V_{DRM}$	max. 50	mA
t_{gd}	$T_{vj} = 25^\circ\text{C}$; $I_G = 1 \text{ A}$; $di_G/dt = 1 \text{ A}/\mu\text{s}$	1	μs
t_{gr}	$V_D = 0,67 \cdot V_{DRM}$	2	μs
$(di/dt)_{cr}$	$T_{vj} = 130^\circ\text{C}$	max. 100	A/ μs
$(dv/dt)_{cr}$	$T_{vj} = 130^\circ\text{C}$; SKT ...D / SKT ...E	max. 500 / 1000	V/ μs
t_q	$T_{vj} = 130^\circ\text{C}$;	120	μs
I_H	$T_{vj} = 25^\circ\text{C}$; typ. / max.	150 / 250	mA
I_L	$T_{vj} = 25^\circ\text{C}$; $R_G = 33 \Omega$; typ. / max.	300 / 600	mA
V_{GT}	$T_{vj} = 25^\circ\text{C}$; d.c.	min. 3	V
I_{GT}	$T_{vj} = 25^\circ\text{C}$; d.c.	min. 200	mA
V_{GD}	$T_{vj} = 130^\circ\text{C}$; d.c.	max. 0,25	V
I_{GD}	$T_{vj} = 130^\circ\text{C}$; d.c.	max. 10	mA
$R_{th(j-c)}$	cont.	0,16	K/W
$R_{th(j-c)}$	sin. 180	0,18	K/W
$R_{th(j-c)}$	rec. 120	0,2	K/W
$R_{th(c-s)}$		0,03	K/W
T_{vj}		- 40 ... + 130	$^\circ\text{C}$
T_{stg}		- 55 ... + 150	$^\circ\text{C}$
V_{isol}		-	V~
M_s	to heatsink	30	Nm
a		5 * 9,81	m/s ²
m	approx.	250	g
Case		B 6	



SKT




Fig. 1L Power dissipation vs. on-state current




Fig. 1R Power dissipation vs. ambient temperature




Fig. 2 Rated on-state current vs. case temperature




Fig. 3 Recovered charge vs. current decrease




Fig. 4 Transient thermal impedance vs. time







Fig. 5 Thermal resistance vs. conduction angle







Fig. 9 Gate trigger characteristics



* The specifications of our components may not be considered as an assurance of component characteristics. Components have to be tested for the respective application. Adjustments may be necessary. The use of SEMIKRON

products in life support appliances and systems is subject to prior specification and written approval by SEMIKRON. We therefore strongly recommend prior consultation of our personal.