


**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** **1600280017**  
**Status:** **Active**  
**Overview:** stAK50h Connection System  
**Description:** stAK50h Hybrid Receptacle, 32 Circuits, Key 7, Rib Option B, Light Brown, Bag

**Documents:**

<a href="#">3D Model</a>	<a href="#">Application Specification AS-160014-001-001 (PDF)</a>
<a href="#">3D Model (PDF)</a>	<a href="#">Packaging Specification PK-31302-266-001 (PDF)</a>
<a href="#">Drawing (PDF)</a>	<a href="#">Test Summary 1600140000-TS-000 (PDF)</a>
<a href="#">Product Specification 1600140001-000 (PDF)</a>	<a href="#">Datasheet (PDF)</a>
<a href="#">Product Specification 1600140002-PS-000 (PDF)</a>	<a href="#">RoHS Certificate of Compliance (PDF)</a>



**General**

Product Family	Crimp Housings
Series	160028
Application	Automotive, Power, Signal, Wire-to-Board
Overview	stAK50h Connection System
Product Name	stAK50h
UPC	193264073191

**Physical**

Circuits (maximum)	32
Color - Resin	Brown (Light)
Gender	Receptacle
Glow-Wire Capable	No
Keying to Mating Part	Yes
Lock to Mating Part	Yes
Material - Resin	SPS
Net Weight	5.401/g
Number of Rows	5
Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface	2.00mm, 4.00mm
Pitch - Termination Interface	2.00mm, 4.00mm
Polarized to Mating Part	Yes
Ports	1
Stackable	No
Temperature Range - Operating	-40° to +85°C

**Material Info**

**Reference - Drawing Numbers**

Application Specification	AS-160014-001-001
Packaging Specification	PK-31302-266-001
Product Specification	1600140001-000, 1600140002-PS-000
Sales Drawing	1600280011-000, SD-160028-002-001
Test Summary	1600140000-TS-000

**EU ELV**

**Compliant**

**EU RoHS**

**Compliant**

**REACH SVHC**

Not Contained Per -  
D(2020)4578-DC (25  
June 2020)

**Halogen-Free**

**Status**

**Low-Halogen**

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

**China RoHS**

Green Image

Compliant

Not Contained

**Search Parts in this Series**

160028 Series

**Use With**

TE NanoMQS 0.50mm Terminal|Delphi  
OCS 1.20mm Terminal|JST MSA 1.20mm  
Terminal