

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [1601126031](#)
Status: **Active**
Overview: [MX150 Sealed and Unsealed Connector System](#)
Description: MX150 Hybrid Mat-Sealed Male Connector Assembly, Dual Row, 12 Circuits, UL 94V-0, Keying Option A, Positions 1, 3, 7, and 11 Blocked, Black

Documents:

[Drawing \(PDF\)](#) [Datasheet \(PDF\)](#)
[Product Specification 1601110001-PS-000 \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)
[Application Specification 1601110001-AS-000 \(PDF\)](#)

General

Product Family [Crimp Housings](#)
Series [160112](#)
Application [Power, Wire-to-Wire](#)
More Detailed Tech Information [http://uscar.org/guest/teams/10/Electrical-Wiring-Component-Applications -Partnership](http://uscar.org/guest/teams/10/Electrical-Wiring-Component-Applications-Partnership)
Overview [MX150 Sealed and Unsealed Connector System](#)
Polarization [A](#)
Product Name [MX150](#)
UPC [191130340545](#)

Physical

Circuits (maximum) [12](#)
Color - Resin [Black](#)
Gender [Plug](#)
Glow-Wire Capable [No](#)
Keying to Mating Part [Yes](#)
Lock to Mating Part [Yes](#)
Material - Resin [Nylon](#)
Net Weight [22.660/g](#)
Number of Rows [2](#)
Packaging Type [Bag](#)
Panel Mount [No](#)
Pitch - Mating Interface [3.50mm](#)
Polarized to Mating Part [Yes](#)
Stackable [No](#)
Temperature Range - Operating [-40° to +125°C](#)

Material Info

Engineering Number [CVP-1601126031](#)

Reference - Drawing Numbers

Application Specification [1601110001-AS-000](#)
Product Specification [1601110001-PS-000](#)
Sales Drawing [1601120000-000](#)



EU ELV

Compliant

EU RoHS

Compliant

REACH SVHC

Not Contained Per -
D(2020)4578-DC (25
June 2020)

Halogen-Free

Status

Low-Halogen

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

China RoHS

Green Image

Compliant

Not Contained

Search Parts in this Series

[160112](#) Series

Mates With

MX150 Hybrid Sealed Female Connector Assembly [160111](#)

Use With

MX150 Male Terminal [33000](#) , [33011](#) ,
Industry Standard Terminal 2.80mm