

Contact insert - VC-TFS 4 - 1607460

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Contact insert with integrated sleeve frame, without PE plate, design: VC 2, with screw terminal blocks, 4-pos.

Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	41.47 g
Custom tariff number	85366990
Country of origin	Poland

Classifications

eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209

ETIM

ETIM 2.0	EC000438
ETIM 3.0	EC000438
ETIM 4.0	EC000438
ETIM 5.0	EC000438

UNSPSC

UNSPSC 6.01	30211923
UNSPSC 7.0901	39121522
UNSPSC 11	39121522
UNSPSC 12.01	39121522
UNSPSC 13.2	39121522

Contact insert - VC-TFS 4 - 1607460

Approvals

Approvals


Approvals


UL Recognized / cUL Recognized / cULus Recognized


Ex Approvals

Approvals submitted

Approval details

UL Recognized 	
mm ² /AWG/kcmil	20-6
Nominal current I _N	55 A
Nominal voltage U _N	600 V

cUL Recognized 	
mm ² /AWG/kcmil	20-6
Nominal current I _N	45 A
Nominal voltage U _N	600 V

cULus Recognized 	
--	--