

Cable connector - CA-17P1N128006



1619729

<https://www.phoenixcontact.com/pc/products/1619729>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Cable connector, CA, straight, shielded: yes, Screw locking, M23, No. of pos.: 17, Direction of rotation: Standard, type of contact: Pin, Solder connection, cable diameter range: 4 mm ... 6 mm, coding:N

Your advantages

- Safe use in the field, thanks to high degree of protection
- Connector for flexible on-site assembly
- Consistent EMC protection for reliable transmission of signals
- Solder connection: proven connection technology for various litz wires

Cable connector - CA-17P1N128006



1619729

<https://www.phoenixcontact.com/pc/products/1619729>

Commercial Data

Item number	1619729
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to Order (non-returnable)
Product Key	ABRBFA
Catalog Page	Page 87 (C-2-2019)
GTIN	4046356821889
Weight per Piece (including packing)	95 g
Weight per Piece (excluding packing)	93 g
Customs tariff number	85366990
Country of origin	DE

Cable connector - CA-17P1N128006



1619729

<https://www.phoenixcontact.com/pc/products/1619729>

Technical Data

Product properties

Product type	Circular connector (cable-side)
--------------	---------------------------------

Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C
---------------------------------	-------------------

Connector

Insulating body

Coding	N
Insulation body material	PBT
Contact material	CuZn
Contact surface material	Ni/Au
Insertion/withdrawal cycles	100
Connection method	Solder connection
Contact type	Pin
Application	Signal
Number of positions	17
Direction of rotation	Standard
Connection profile	17
Rated surge voltage	1.5 kV 1.5 kV
Overvoltage category	III III
Degree of pollution	3 3

Housing

Type of locking	Screw locking
Thread type	M23
Degree of protection	IP67
Housing material	Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)

Seal

Seal material	NBR
External cable diameter	4 mm ... 6 mm

Cable connector - CA-17P1N128006


1619729

<https://www.phoenixcontact.com/pc/products/1619729>



Drawings

Dimensional drawing




Cable connector - CA-17P1N128006




1619729

<https://www.phoenixcontact.com/pc/products/1619729>

Approvals

 cUL Recognized Approval ID: E335019-20141210				
	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	48 V	5 A	- 18	-

 UL Recognized Approval ID: E335019-20141210				
	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	48 V	8 A	- 18	-

cULus Recognized

Cable connector - CA-17P1N128006



1619729

<https://www.phoenixcontact.com/pc/products/1619729>

Classifications

ECLASS

ECLASS-9.0	27440102
ECLASS-10.0.1	27440102
ECLASS-11.0	27440102

ETIM

ETIM 8.0	EC002635
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

Cable connector - CA-17P1N128006



1619729

<https://www.phoenixcontact.com/pc/products/1619729>

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Cable connector - CA-17P1N128006

1619729

<https://www.phoenixcontact.com/pc/products/1619729>



Accessories

Torque screwdriver

Torque screwdriver - SF-Z0028 - 1607456

<https://www.phoenixcontact.com/pc/products/1607456>

Torque screwdriver, series: RC



Hook wrench

Hook wrench - SF-Z0027 - 1607455

<https://www.phoenixcontact.com/pc/products/1607455>

Hook wrench, series: RC



Cable connector - CA-17P1N128006

1619729

<https://www.phoenixcontact.com/pc/products/1619729>

Protective cap

Protective cap - RC-Z2058 - 1604223

<https://www.phoenixcontact.com/pc/products/1604223>

Plastic protection cap for connectors with M23 knurled nut



Plastic anti-static dust protection cap

Plastic anti-static dust protection cap - RC-Z2468 - 1611796

<https://www.phoenixcontact.com/pc/products/1611796>

Plastic protection cap, antistatic, for connectors with M23 knurled nut



Cable connector - CA-17P1N128006

1619729

<https://www.phoenixcontact.com/pc/products/1619729>

Color-coding

Color-coding - RF-Z0014 - 1620588

<https://www.phoenixcontact.com/pc/products/1620588>

Color-coding, color: green



Color-coding

Color-coding - RF-Z0015 - 1620592

<https://www.phoenixcontact.com/pc/products/1620592>

Color-coding, color: orange



Cable connector - CA-17P1N128006

1619729

<https://www.phoenixcontact.com/pc/products/1619729>

Color-coding

Color-coding - RF-Z0016 - 1620593

<https://www.phoenixcontact.com/pc/products/1620593>

Color-coding, color: black



Square mounting flange

Square mounting flange - RF-Z0003 - 1607905

<https://www.phoenixcontact.com/pc/products/1607905>



Square mounting flange, Axial seal, 4xM3, flange dimensions: 35 mm x 35 mm, series: RF

Cable connector - CA-17P1N128006

1619729

<https://www.phoenixcontact.com/pc/products/1619729>



Metal protective cap

Metal protective cap - CA-Z0077 - 1627224

<https://www.phoenixcontact.com/pc/products/1627224>



Metal protection cap with steel wire and loop, for M23 signal connectors with knurled nut for fastening to the cable

Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachsmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

info@phoenixcontact.com