

# 404802803029 Product Details

[Live Product Chat](#)



**404802803029**  
(1625932-8)

TE Internal Number: 1625932-8

[Active](#)

## Variable Resistors

[Converted to EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

### Product Highlights:

- Variable Resistor
- Resistor Type = Potentiometer
- Resistance Selection = K ?
- Resistance = 10K ?
- Power Rating = 1.00 W

[View all Features](#)

## Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

## Documentation & Additional Information

### Product Drawings:

- None Available

### Catalog Pages/Data Sheets:

- [Type L Series Spindle Operated Potentiometers](#) (PDF, English)

### Product Specifications:

- None Available

### Application Specifications:

- None Available

### Instruction Sheets:

- None Available

### CAD Files:

- None Available

### Additional Information:

- [Product Line Information](#)

### Related Products:

- [Tooling](#)

[List all Documents](#)

## Product Features (Please use the Product Drawing for all design activity)

### Product Type Features:

- Product Type = Variable Resistor
- [Resistor Type](#) = Potentiometer
- [Resistance \(?\)](#) = 10K
- [Element](#) = Cermet
- [Sealed](#) = Yes
- [Mount Angle](#) = Vertical
- [Termination Type](#) = PCB Terminations

### Electrical Characteristics:

- Resistance Selection (?) = K
- [Power Rating \(W\)](#) = 1.00
- [Tolerance \(%\)](#) = 10

### Termination Related Features:

- [Termination Post Orientation](#) = 5.0 x 5.0

### Body Related Features:

- [Series](#) = L
- [Shaft Style](#) = Slotted, 22mm
- [Package, Component Size](#) = 13

### Configuration Related Features:

- [Sections](#) = Single
- [Adjustment Location](#) = Top
- [Adjustment Style](#) = Spindle
- [Operating Function](#) = Single Turn

### Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C, Reflow solder capable to 260°C, Pin-in-Paste capable to 245°C, Pin-in-Paste capable to 260°C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

### Other:

- Brand = Citec

[Provide Website Feedback](#) | [Need Help?](#)