




Plastic hood
with straight cable exit
and jack screws



(click on the schematic(s) for a more detailed view)



PDF drawings

Part number	PDF-format drawing
165X10139XE	16K1A1078.pdf
165X10149XE	16K1A1078.pdf
165X10159XE	16K1A1078.pdf
165X10169XE	16K1A1078.pdf
165X10179XE	16K1A1078.pdf
165X10909XE	16K1A1730.pdf
165X10919XE	16K1A1730.pdf
165X10929XE	16K1A1730.pdf

Please contact Conec for any missing PDF drawings

No. of Pos.	A	B	C	D	E	ØF
9	34.0	25.0	25.0	27.75	14.5	8.5
15	42.3	33.3	37.0	39.75	14.5	10.0
25	56.0	47.0	37.0	39.75	14.5	10.5
37	72.5	63.5	37.0	39.75	14.5	10.5
50	70.0	61.1	50.0	50.0	21.0	10.5

The hood with top cable entry consists of two half shells in which the screws are firmly inserted on one side each. The cable clamp is integrated in the hood. The hood is available either with screw thread UNC 440 or M 3.

Technical Data:

Hood: Polyamid + GF / black / grey

ABS V -O / metallized

Screws: brass, nickel -plating

Part Numbers						
Bulk packaged hoods. For single packaged add letter "E" on the end of part number.						
	black		grey		metallized	
No. of Pos.	4-40 UNC	M3	4-40 UNC	M3	4-40 UNC	M3
9	165X10139X	165X10189X	165X14109X	165X14159X	165X10909X	165X10959X
15	165X10149X	165X10199X	165X14119X	165X14169X	165X10919X	165X10969X
25	165X10159X	165X10209X	165X14129X	165X14179X	165X10929X	165X10979X
37	165X10169X	165X10219X	165X14139X	165X14189X	165X10939X	165X10989X
50	165X10179X	165X10229X	165X14149X	165X14199X	165X10949X	165X10999X