

4

3

2

1

used for:

D-SUB

F

F

E

E

D

D

C


C

B


B

A

A



(b)



(c)

Part NO. Bulk package	Part NO. Single package
165X11049X	165X11049XE

Directive 2002/95/EC
„RoHS“
Compliant

NOTES:

- HOOD MATERIAL: ABS V0 / METALLIZED
- SCREWLOCK: MATERIAL: BRASS NICKEL-PLATING

THIS DRAWING MAY NOT BE COPIED OR
REPRODUCED IN ANY WAY, AND MAY NOT
BE PASSED ON TO A THIRD PARTY WITHOUT
WRITTEN PERMISSION.
OWNERSHIP AND COPYRIGHT OF CONEC GmbH
DO NOT ALTER CAD DRAWING BY HAND

1 x c	Ä3792	27.10.2010	K.H.
2 x b	Ä 2286	02.08.2005	HS
rev.	description	date	name

tolerance

2002

date

name

drawn

04.03.

Schmidt


appd.

04.03.

Mickenbecker

norm

d-old



scale:

1:1

material:

SEE NOTES

title:

Plastic Hood
with straight cable exit
and screw lock, 50 pos.

dwg no:

AutoCAD 2000

DIN-A

16K2A670 (b)

4

sh: 1/1

part no:

SEE TABLE

CONEC®

4

3

2

1