



(c) NOTES:

1. METAL SHELLS: COPPER ALLOY;
min. 315µm TIN over 40-80µm NICKEL
2. INSULATOR: TPE
3. CLAMPS: STAINLESS STEEL
4. SCREW: STAINLESS STEEL

(d) 5. CONNECTOR IS PART MARKED: PART NO. CONEC ABC

Directive 2002/95/EC
„RoHS“
Compliant

Part No.	No. of pos.	A ^{-0,76}	B ^{+0,25}	C	D ^{-0,3}	(d) E ⁺²⁵	(d) F ^{-0,76}
165X14719X	9	31,19	16,79	25,00 ^{+0,12 -0,10}	6,12	8,23	12,93
165X14729X	15	39,52	25,12	33,30 ^{+0,15}	6,12	8,23	12,93
165X14739X	25	53,42	38,84	47,04 ^{±0,13}	5,99	8,23	12,93
165X14749X	37	69,70	55,30	63,50 ^{+0,13 -0,11}	5,99	8,23	12,93
165X14759X	50	67,31	52,68	61,10	5,99	10,95	15,75

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH

DO NOT ALTER CAD DRAWING BY HAND

				tolerance		dim. in mm	
				date	name		
				drawn	10.09.2001	E.Mickenbecker	
				appd.	10.09.2001	A.Mickenbecker	
3 x d	Ä3662	23.08.2010	K.H.	norm	DIN 41652		
1 x c	Ä1912	06.04.2004	Lehmen	d-old			
3 x b	Ä1788	06.06.2004	Lehmen				
a	Origin						
rev.	description	date	name	CONEC ©			

scale:	2:1		
material:	SEE NOTES		
title:	HOOD 9 - 50pos. FOR SOCKET CONNECTOR water resiatant, shielded for EMI/RFI		
dwg no:	Inventor 10	DIN-A4	
	16K1A291A	sh: 1	
part no:	SEE TABLE		

