



- Notes:**
- Electrical Specifications:
    - Meets EIA/TIA-568-B.2 Cat.5e Specification
    - Contact Resistance: 20mOhm max.
    - Insulation Resistance: 500MOhm min. @ 100 VDC
    - Current Rating: 1.2A max. at 25° C
    - Working Voltage: 100 VDC
    - DWV: 1000 VDC/60s Contact to Contact, 1500 VDC/60s Contact to Metal Shell
    - Operating Temperature: -40° C to +85° C
  - Material and Finish:
    - Receptacle Housing: Polyester (Color: See Part Number Table); UL94 V-0
    - Cover Coupling Ring: Polyester (Black); UL94 V-0
    - Panel Nut: Brass, Finish: Nickel Plated
    - Panel Gasket: Silicon, Color: White
    - Cover Gasket: Silicon, Color: White
    - Tether: Polycarbonate, Color: Black
    - Cat.5e RJ45 IDC Jack Metal Shell: Copper Alloy, Nickel Plated
    - Cat.5e RJ45 IDC Jack Plastic Housing: Glass filled PBT UL94 V-0, Color: Black
    - Cat.5e RJ45 IDC Jack Contacts: Phosphor Bronze, Finish: 50u" Gold min. over Nickel
  - Connector can be front or rear mounted to a maximum panel thickness of 3.2mm.
  - IP67 rated when covered or fully mated with the appropriate mating connector

RoHS compliant

Description	Colored Plastic Receptacle Housing with Shielded Cat.5e RJ45 IDC Jack + Black Cover					
Plastic Receptacle Housing Color	Black	Blue	Green	Yellow	Red	White
Part Number	17-10021	17-102664	17-102674	17-102684	17-102694	17-102704

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY MANNER WITHOUT THE WRITTEN PERMISSION OF CONEC CORPORATION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION.	Customer:			Tolerance Unless otherwise specified 0 PLC ±0.50 1 PLC ±0.38 2 PLC ±0.25 3 PLC ±0.10 ANGLES ±3°			Scale: 1.2:1	Dim. in mm
	Name	Title	Approval Date	2011	Date		Name	Material: See Notes
					Draw.	Jan. 28	Vincent Ke	<b>Receptacle &amp; Cover Assembly Kit</b> Colored Plastic Receptacle Housing with Shielded Cat. 5e RJ45 IDC Jack
					Appd.	Jan. 28	J. Chaudry	
				Norm			Drawing No.: 17K1A194	DIN A3
	1 x c	A21-0426	29.10.2021	Bub	D-old		Part No.: SEE PART NUMBER TABLE	Sheet 1/1
	b		Mar/08/2011	Vincent ke				
	a	original						
	Rev	Changes	Date	Name				